

## Specifications

Product Line	Woodland Collection
Product Type	Stone Polymer Composite
Core Material	Rigid Polymeric Core
Wear Layer	20mil
Overall Thickness	6.0mm
Nominal Plank Size	7" x 48"
Actual Plank Size	180 mm x 1220 mm
Edge Profile	Matte Bevel
Embossing	Natural Wood Texture
Finish	UV Coated Matte Finish
Installation Type	Floating   2G Valinge
Attached Pad	1.0mm IXPE Sound Reducing

## Shipping

### CARTON

Planks	8
Square Feet	18.70
Weight (lbs)	42
Square Meters	1.737
Weight (kg)	19.05

### PALLET

Cartons	55
Square Feet	1,028.50
Weight (lbs)	2,240
Square Meters	95.551
Weight (kg)	1,016.05

### CONTAINER

Cartons	1,430
Square Feet	26,741.00
Weight (lbs)	58,240
Square Meters	2,484.326
Weight (kg)	26,417.22

## Warranty



**30 YEAR  
RESIDENTIAL**



**10 YEAR  
COMMERCIAL**



WATERPROOF  
MATERIAL



UNIQUE PLANK  
PATTERN VARIATION



SCRATCH &  
STAIN RESISTANT

## Performance Testing

Slip Resistance	ASTM D2047	R9   Class DS
Castor Chair	EN 426	PASS (18,000 Cycles)
Dimensional Stability	ISO 23999	PASS
Light Resistance	ASTM F1515	PASS
Heat Resistance	ASTM F1514	PASS
Fire Resistance and Smoke Emission	EN ISO 9239-1	Class Bfl s1
Chemical Resistance	ASTM F925	PASS
Phthalate Content	CPSC-CH-C1001-09.3	Not Detected
Heavy Metals	ASTM F963	PASS
VOC Emission	BS ISO 16000 / ASTM D5116	Certified FloorScore & GreenGuard Gold
Vinyl Chloride Monomer (VCM) Content	ASTM D4443-95(2002)	Not Detected

## Sound Testing

Sound testing was conducted over a 150mm thick concrete floor and the 5.0mm SPC Flooring (including 1mm IXPE underlayment) were placed on the concrete floor.

Delta Impact Sound Insulation Class	ASTM E2179-09	$\Delta$ IIC = 20
Impact Sound Insulation Class (IIC)	ASTM E492-09	IIC = 64
Sound Transmission Class (STC)	ASTM E413-22	STC = 52