



INSTALLATION INSTRUCTIONS

STAINLESS STEEL UNDERMOUNT SINKS



www.buildpelican.com



STAINLESS STEEL UNDERMOUNT SINKS INSTALLATION INSTRUCTIONS

BEFORE INSTALLATION:

- Read instructions carefully before installation. Inspect sink for any damages. Do not install damaged sink as this will void the warranty.
- Pelican Int'l recommends that installation be done by a licensed professional installer.
- Pelican recommends that sink cut out and mounting holes be cut by the countertop fabricator prior to installation.
- If you purchased a handmade sink, a template was provided. For all other undermount stainless steel sinks, a template is available upon request. Installers can retrieve desired DXF files for all undermount stainless steel sinks from our website: www.buildpelican.com
- Pelican is not responsible for improper sink or countertop installation. Pelican is not liable for any damages to sink, countertops, or personal injury during installation.
- Pelican undermount sinks should only be fastened to a solid surface countertop (i.e. quartz, granite, etc).
- Follow all local plumbing and building codes.

INSTALLATION PROFILES:

Alignment of sink to cut out is vital for a proper fit and finished look. Based upon your own aesthetic preference, Pelican undermount stainless steel sinks can be installed flush mount, reveal, or overhang.

FLUSH MOUNT

Countertop meets the edge of the sink, creating a flush fit with the sink bowl.



REVEAL

Countertop edge sits slightly back from the edge of the sink and exposes sink rim.



OVERHANG

Countertop extends slightly over the edge of sink on all sides.



STAINLESS STEEL UNDERMOUNT SINKS INSTALLATION INSTRUCTIONS

STEP 1:

- Fasten mounting brackets loosely into the pre-drilled mounting holes in the countertop.

STEP 2:

- Clean underside of countertop and rim of the sink.
- Apply good quality silicone caulk evenly around the top of the sink flanges.
- Position and align the sink under the countertop opening. Press the silicone and flange up onto the countertop.
- Check alignment of sink to countertop opening and move slightly if needed.

STEP 3:

- From the underside, gently tighten the fasteners with a screw driver until the sink is snug against the countertop.
- Check alignment of the sink in the countertop opening and then tighten fasteners until the sink is tight against the countertop. Do not overtighten.
- Wipe away excess silicone caulk with rag.

FLUSH MOUNT INSTALLATION EXAMPLE

