

**PVC
TERMINATION
VENT SCREEN
4818-SCRN**

The NIBCO® PVC Termination Vent Screen can be installed into high-efficiency appliance vent lines with a push or interference fit. The screen protects the appliance from intrusion of rodents. The stainless steel screen is corrosive resistant and includes a 1/4" mesh opening for maximum air flow.

The interference fit makes it easy to install and easy to remove during freezing temperatures when the condensation might freeze the opening shut.

PLASTIC FITTINGS

FEATURES

- Use with High-Efficiency Appliance Vent Lines
- Prevent Rodents from Entering the Pipes
- Permits Maximum Air Flow
- Interference Fit with ABS or PVC DWV Sockets
- No Solvent Cement or Glue Required

MATERIALS & CONSTRUCTION

- PVC Spigot
- Stainless Steel Screen
- 1/4" Mesh Opening

CAUTIONS

- Not Intended or Certified for Roof Vents
- Remove During Freezing Temperatures
- Do not Install with Solvent Cement or Glue



4818-SCRN
2", 3", 4"



Size	Materials	Weight (lbs)	Outside Diameter	Width
2"	PVC / SST	0.07	2.38"	1.08"
3"	PVC / SST	0.15	3.50"	1.08"
4"	PVC / SST	0.22	4.50"	1.08"