

VORNOI I

2W | 100 lm | 2200K

VORN-I-2W-2200K-E27-T

Voronoï I 2W 2200K E27 Tinted LED Bulb


tala®

The Voronoï I bulb was designed to imitate forms and shapes found in nature. Mouth-blown and assembled by hand to the highest standards by skilled artisans, this sculptural bulb is best when hung in clusters of three or displayed individually in decorative fixtures. Fitted with E27 base cap.




PHYSICAL

Bulb diameter:	125mm
Bulb length:	175mm
Glass shape:	G125*
Base:	E27
Materials:	Glass & nickel
Glass finish:	Tinted
Weight:	160g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80
— C0/C20

IES/LDT photometry files
and product photography
available on request



ELECTRICAL

Power:	2W
Current:	0.01A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	50 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2200K
Lumens:	100 lm
Incandescent equiv.:	12W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	80
TM30 - Rg	100
TM30 - Rf	94



DIMMING

Dimmable 0-100%
Recommended dimmer: Varilight V-Pro
(For a full list of recommended and compatible dimmers see website)

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 6
Gross weight: 190	Gross weight: 4.485
L 175 x W 175 x H 220mm	L 540 x W 360 x H 240cm

WARRANTY

2 years

EAN

5060400151875

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40
Nieuwegein 3437 JN

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights