


# LIGHT ENGINE II


tala

20W | 1700 lm | 2000-3000K

T35-20W-2000-3000K-E27-SMD



IES/LDT photometry files  
and product photography  
available on request



## PHYSICAL

Bulb dimension:	L 35 mm x H 150 mm
Glass shape:	T35
Base:	E27
Materials:	Ceramic, polycarbonate and steel
Glass finish:	Clear
Weight:	227g
Max. working temp.:	50°C
IP rating:	IP20

## ELECTRICAL

Power:	20W
Current:	0.1 A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.8
Efficiency:	85 lm/W
Lifetime:	30,000 hrs

## ILLUMINATION

CCT:	2000-3000K
Lumens:	1700 lm
Incandescent equiv.:	110 W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	85
TM30 - Rg	90
TM30 - Rf	100

## DIMMING

Dimmable 0-100%  
Recommended dimmer: Varilight V-Pro  
(For a full list of recommended and compatible  
dimmers see website)

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40  
Nieuwegein 3437 JN

tala.co.uk | hello@tala.co.uk | +44 7700 170343724-8111

## WARRANTY

2 years

## EAN

5061046292106

Specification subject to change without  
notice. Refer to our website for the most  
recent product documentation. Tala  
designs in the EU/UK are protected by  
registered and or unregistered design rights