

THE MUSE PORTABLE LAMP IN SOLID BRASS

tala.


SKU: MUSE-PBL-SB-01

FINISH: SOLID BRASS

Cast in signature solid brass, this is a special edition of The Muse by Tala. Recalling the promise and grandeur of the British pleasure garden, The Muse mixes the classic lantern aesthetic with ultra-modern technology. Designed for repairability, it features cordless long-life battery, Dim to Warm LED technology and a custom integrated dimmer. Rated IP44, Tala's first truly portable lamp is suitable for even the British outdoors. Solid Brass is a core tenet of the Tala design canon. The vivid satin sheen and fine-brushed texture evoke a gold-like extravagance, which is further enhanced by its heavy weight.



338mm / 13 3/8"



Ø 125mm / 4 7/8"

PHYSICAL

Dimensions:	Ø12.5 x 33.8cm Ø5 x 13.3in
Materials:	Solid Brass and borosilicate glass
Finish:	Solid Brass
Bulb Finish:	Matte White
Weight:	2500g
IP rating:	IP44 - Suitable for wet locations
Base:	E27 (Lamp only replaceable with 12V Tala Muse bulb)

ELECTRICAL

Appliance class:	Class III
Power:	6W 12V Bulb
Voltage:	5V/2A USB Type-C 5W wireless
Battery:	Li-ion 13.2Ah 3.7V 48.8Wh

ILLUMINATION

CCT:	2000 - 2800K
Lumens:	400lm
Flicker:	<1%
Beam angle:	360°
Light source:	LED
CRI:	97Ra



DIMMING

Yes, rotary dimmer built into fixture.

The battery, glass and light source can all be easily replaced. For replacement parts, please visit our website or contact us at customerservice@tala.co.uk

WARRANTY

2 years

EAN



5060915711731

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40
Nieuwegein 3437 JN

tala.co.uk | hello@tala.co.uk | +44 7700 170343


Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights



2000K (min power)
 Colour fidelity (Rf) 92
 Colour Gamut (Rg) 98

2800K (max power)
 Colour fidelity (Rf) 93
 Colour Gamut (Rg) 103



THE MUSE, CCT VS LIGHT OUTPUT




COLOUR QUALITY METRICS

	Ra (CRI)	R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
2000K	96	96	98	98	95	96	97	93	85	90	95	96	90	96	99	91
2800K	97	96	99	97	95	96	95	90	99	95	98	97	92	98	99	90

SPECTRAL POWER DISTRIBUTION




At 2000K (min power)



At 2800K (max power)

LIGHT OUTPUT VS BATTERY LIFE



The product is designed to work with the custom Tala 12V LED bulb provided. For replacements, visit the Tala website or contact us for assistance.

The product is designed for operation up to 35°C ambient temperature

CONFORMS TO THE FOLLOWING STANDARDS:

IEC 62133-2:2017
 IEC 60598-2-4:2017
 IEC 60598-1:2014+AMD1:2017
 AS 60598-2-4:2019
 AS/NZS 60598-1:2017+A1:2017
 EN 55015:2013+A1:2015

EN 61000-3-2:2014
 EN 61000-3-3:2013
 EN 61547:2009
 EN 60598-2-4:2018
 EN 60598-1:2015+A1:2018
 FCC Part 15 Subpart B Class B

UL 153:2014 Ed. 13+R:24 July 2020
 UL 2054:2004 Ed.2+R:14Sept2011
 UL 1310:2018 Ed. 7+R:16Aug2019
 UL 8750:2015 Ed. 2+R:05Jan2021
 UL 2738:2018 Ed. 2
 CSA C22.2 No. 250.13:2020 Ed. 4+U1
 CSA C22.2 No. 223:2015 Ed. 3
 CSA C22.2 No. 250.4:2020 Ed. 2



Scan me for more technical help