

# GLOBE

6W | 600 lm | 2500K

GLOB-6W-2500K-E27-NT

Globe 6W 2500K E27 Non-Tinted LED Bulb


tala.

The Globe light bulb by Tala features eight exposed sapphire substrate filaments, which come together in this traditional Edison-style shape. The effect is a warm, ambient light in a E27 base that makes the Globe ideal to fit into new or existing fixtures. Suitable for display or behind a shade, the Globe is complete with energy efficient LED technology, lasting an average of 5-10 years based on daily usage.




## PHYSICAL

Bulb diameter:	60mm
Bulb length:	108mm
Glass shape:	A60
Base:	E27
Materials:	Glass & nickel
Glass finish:	Clear
Weight:	31g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— C0/C80  
— C0/C270

IES/LDT photometry files  
and product photography  
available on request



## ELECTRICAL

Power:	6W
Current:	0.03A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	100 lm/W
Lifetime:	30,000 hrs

## ILLUMINATION

CCT:	2500K
Lumens:	600 lm
Incandescent equiv.:	48W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	70
TM30 - Rg	98
TM30 - Rf	90



## DIMMING

Dimmable 0-100%  
Recommended dimmer: Varilight V-Pro  
(For a full list of recommended and compatible dimmers see website)

## LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 70	Gross weight: 0.65
L 63 x W 63 x H 130mm	L 340 x W 140 x H 145cm

## WARRANTY

2 years

## EAN

5060400150991

Tala Energy Ltd. 25b Vyner Street,  
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40  
Nieuwegein 3437 JN

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without  
notice. Refer to our website for the most  
recent product documentation. Tala  
designs in the EU/UK are protected by  
registered and or unregistered design rights