

SSB

LITHIUM STARTING



LIFePO4

- Ultra High Performance
- Designed to be extremely light
- Australia's highest Cranking Batteries
- Higher Reserve Capacity
- Extremely Quick Recharge Time
- High Rate Discharge Lithium Cells
- Design & Built Tough for Australian Conditions
- Direct Fit Replacement
- Ultra Light Weight
- Superior Design & Quality - Manufactured to Quality Assurance Standard ISO 9001



Designed
For Australian
Conditions



Stop Start



Ultra High
Performance



Lithium



Long Life
Design



Sealed Design



Ultra
Lightweight

QUALITY ASSURANCE
ISO 9001

www.superstart.com.au





*For warranty conditions
Please visit our website for
more information

SSB Lithium Starting Batteries are extremely light weight batteries designed for starting applications and are completely dry battery making them spill-proof and leak-proof. You must pick one up for yourself to truly understand how light they are compared to normal lead-acid batteries.

Unlike many other lithium batteries, SSB Lithium Batteries are made using prismatic cells making them not only safe to use, but also boasts higher CCA (cold cranking amps), better cyclic properties and longer life. SSB Lithium Starting Battery range is the pioneer of lithium starting batteries in Australia. Our cutting-edge research and technology have been leaders in Australia in innovating, researching, and testing lithium batteries for over 12 years. We have also purchased and tested almost every other major brand of lithium starting batteries from around the world and have designed SSB Lithium Starting Batteries to be superior in every aspect.

SSB Lithium Starting Batteries are the most powerful and lightest starting batteries in the world. While other brands may use similar battery cases and colours, be assured that if it does not have the SSB logo, it does not offer the same capacity as our lithium batteries. SSB Lithium Starting Batteries come with a true industry leading 3 Year Full Replacement Warranty*.

Specifications

MODEL	VOLTS	CCA	AH	RESERVE CAPACITY (mins)	DIMENSIONS				ASSEMBLY FIGURE	TERMINAL TYPE	WEIGHT (KG)
					LENGTH (mm)	WIDTH (mm)	HEIGHT (mm)	TERMINAL HEIGHT (mm)			
LS40ZAL	12	800	30	72	196	127	202	221	— +	Thin Post STD SAE	4.45
LS40TL	12	1000	40	96	237	129	200	221	— +	Thin Post STD SAE	5.74
LS50P	12	1400	60	144	238	174	168	190	+ —	STD SAE	8.00
LS50PL	12	1400	60	144	238	174	168	190	— +	STD SAE	8.00
LS55D23L	12	1400	60	144	238	172	200	221	— +	STD SAE	7.20
LS70	12	1400	60	144	260	172	203	224	+ —	STD SAE	8.60
LS70L	12	1400	60	144	260	172	203	224	— +	STD SAE	8.60
LS70ZZ	12	1600	80	192	305	172	203	224	+ —	STD SAE	10.16
LS70ZZL	12	1600	80	192	305	172	203	224	— +	STD SAE	10.16
LS55T	12	1200	40	144	240	174	190	190	— +	STD SAE	7.20
LS66	12	1400	60	144	278	174	175	175	— +	STD SAE	8.40
LS66T	12	1600	80	192	278	174	190	190	— +	STD SAE	10.65
LS88T	12	1800	100	240	352	174	190	190	— +	STD SAE	13.59

