

Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

C19F 29" Single Solid Door Narrow Depth Reach-In Freezer



FEATURES

- · Stainless steel exterior and interior
- Aluminum back
- · Narrow Depth
- · Refrigeration system keeps food at safe temperatures
- · Self-closing doors with 90 degree stay-open feature
- · Locks and keys included
- · Adjustable heavy-duty PVC coated shelves
- · Recessed door handle
- · Electronic control system
- · Preinstalled heavy-duty casters with brakes
- · Removable installation board
- · Hydro-Carbon R290 refrigerant

This Coldline stainless steel reach-in commercial freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
- ETL Sanitation Listed Conforms to UL & NSF Standards





USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.

USR Brands, Inc.
BRANDS Phone: 800-764-11

Rev. 10-2022



Datasheet

Project:	Quantity:
Model #:	Approval:

For Commercial Use Only

TECHNICAL DATA

DIMENSIONS

Exterior Dimensions	29"W x 25.4"D x 81.5"H
Interior Dimensions	24.4"W x 20.4"D x 59.5"H
Packaging Dimensions	30.3"W x 27.5"D x 85.5"H
Net Volume	15.6 cu. ft.
Unit Weight	253 lb.
Shipping Weight	280 lb.

ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	2.62
Plug Type	NEMA 5-15P
Power Cord Length	96"

COOLING

Temperature Range	-8°F to 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	2/3

CONSTRUCTION

Exterior Material	430 Stainless Steel
Interior Material	430 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Size	3 Qty: 23.4"W x 19.4"D
Shelf Material	Epoxy Coated Wire
Shelf Load Capacity	90 lb.
Adjustable Shelf	Yes
Interior Light	Yes
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

TECHNICAL DRAWING

MODEL: C19F

MFR ITEM #:







