

**Datasheet** 

Project:

Model #:

Approval:

Quantity:

For Commercial Use Only

## C35F 40" Double Solid Door Reach-In Freezer



### **FEATURES**

- · Stainless steel interior and exterior
- Aluminum back
- · Refrigeration system keeps food at safe temperatures
- · Self-closing doors with 90 degree stay-open feature
- Interior light bulb
- · Locks and keys included
- Adjustable heavy-duty PVC coated shelves
- Recessed door handle
- Electronic control system
- Preinstalled heavy-duty casters with brakes
- · Removable installation board
- Hydro-Carbon R290 refrigerant

This Coldline stainless steel reach-in commercial freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

cETLus Listed

• ETL Sanitation Listed Conforms to UL & NSF Standards



USR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.





Datasheet

Project: Model #:

Ċ.

Quantity:

Approval:

For Commercial Use Only

## **TECHNICAL DATA**

#### DIMENSIONS

Exterior Dimensions	40"W x 30"D x 81.5"H
Interior Dimensions	35"W x 24.4"D x 59.5"H
Packaging Dimensions	41"W x 33"D x 86"H
Net Volume	27.6 cu. ft.
Unit Weight	269 lb.
Shipping Weight	309 lb.

#### ELECTRICAL

Voltage	115
Hertz	60
Phase	1
Amps	4.8
Plug Type	NEMA 5-15P
Power Cord Length	96"

### COOLING

Temperature Range	-10°F to 0°F
Refrigerant	R290
Max. Ambient Temp	90°F
Defrosting	Automatic
Temperature Controller	Digital
Horsepower	6/7

#### CONSTRUCTION

Exterior Material	430 Stainless Steel
Interior Material	430 Stainless Steel
Insulation Material	Foamed-in-Place Polyurethane
Shelf Quantity	6
Shelf Material	Epoxy Coated Wire
Shelf Load Capacity	90 lb.
Adjustable Shelf	Yes
Interior Light	Yes
Mobility Wheels/Casters	(4) Qty: 2 with brakes, 2 without

# **TECHNICAL DRAWING**



