

Datasheet

Project:

Model #:

Quantity: Approval:

For Commercial Use Only

## C-2FE 54" Double Solid Door Reach-In Freezer



### FEATURES

- · Stainless steel interior and exterior
- Aluminum back
- Refrigeration system keeps food at safe temperatures
- · Self-closing doors with 90 degree stay-open feature
- · Locks and keys included
- · Adjustable heavy-duty PVC coated shelves
- · Recessed door handle
- Electronic control system
- · Preinstalled heavy-duty casters with brakes
- · Removable installation board
- · Hydro-Carbon R290 refrigerant

This Coldline stainless steel reach-in commercial freezer is perfect for restaurants, delis, bakeries, or cafes. It keeps your food products at safe temperatures.

- cETLus Listed
- ETL Sanitation Listed
  Conforms to UL & NSF Standards



Use SR Brands is a US supplier of premium quality commercial cooking, refrigeration and food preparation equipment. Our aim is simple. Produce industry-leading commercial restaurant equipment at reasonable prices, and back it all up with an easy to understand, no nonsense warranty that people can count on.





**Datasheet** 

Project: Model #:

Q

Quantity:

Approval:

σ

For Commercial Use Only

### **TECHNICAL DATA**

#### DIMENSIONS

| Exterior Dimensions  | 54"W x 32.2"D x 81.5"H |
|----------------------|------------------------|
| Interior Dimensions  | 49.4"W x 27"D x 59.5"H |
| Packaging Dimensions | 56.3"W x 34"D x 84.5"H |
| Net Volume           | 41.3 cu. ft.           |
| Unit Weight          | 448 lb.                |
| Shipping Weight      | 530 lb.                |

#### ELECTRICAL

| Voltage           | 115        |
|-------------------|------------|
| Hertz             | 60         |
| Phase             | 1          |
| Amps              | 6.08       |
| Plug Type         | NEMA 5-15P |
| Power Cord Length | 96"        |

#### COOLING

| Temperature Range      | -8°F to 0°F |
|------------------------|-------------|
| Refrigerant            | R290        |
| Max. Ambient Temp      | 90°F        |
| Defrosting             | Automatic   |
| Temperature Controller | Digital     |
| Horsepower             | 1 2/7       |

#### CONSTRUCTION

| Exterior Material       | 430 Stainless Steel               |
|-------------------------|-----------------------------------|
| Interior Material       | 430 Stainless Steel               |
| Insulation Material     | Foamed-in-Place Polyurethane      |
| Shelf Size              | 6 Qty: 23.6"W x 23.3"D            |
| Shelf Material          | Epoxy Coated Wire                 |
| Shelf Load Capacity     | 90 lb.                            |
| Adjustable Shelf        | Yes                               |
| Interior Light          | Yes                               |
| Mobility Wheels/Casters | (4) Qty: 2 with brakes, 2 without |

# **TECHNICAL DRAWING**

MODEL: C-2FE

| N<br>FRONT VIEW | IEMA 5-15P |
|-----------------|------------|
| FRONT VIEW      |            |
| 54"             |            |
|                 |            |
|                 |            |
| 81.5"           |            |
| 61.5            |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
| SIDE VIEW       |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
| + 3" +          |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |
| TOP VIEW54*     |            |
|                 |            |
| 32.2"           |            |
|                 |            |
| 57"             |            |
|                 |            |
|                 |            |
|                 |            |
|                 |            |

