



## Class 00 Electrical Insulating Gloves

### Applications

- Power Utilities and Public Works
- Electric Public Transport Maintenance
- EV Battery Manufacturing and Assembly
- EV Aftermarket Service and Maintenance
- Excavation and Cable Laying
- Electrical Maintenance
- Cable Jointing
- Field services



Code	Length	Color	Cuff	Cat	Proof	Max	Size**	EN Arc	ATPV Arc Rating
24-9010	11" / 28cm	Red	Straight / Beaded	A/Z/C	2.500/10.000	500/750	7-12	APC 1	8.4 cal/cm²
24-9011	11" / 28cm	Black	Straight / Beaded	A/Z/C	2.500/10.000	500/750	7-12	APC 1	8.4 cal/cm²
24-9012*	11" / 28cm	Yellow	Straight / Beaded	A/Z/C	2.500/10.000	500/750	7-12	APC 1	8.4 cal/cm²
24-9020	14" / 36cm	Red	Straight / Beaded	A/Z/C	2.500/10.000	500/750	7-12	APC 1	8.4 cal/cm²
24-9021	14" / 36cm	Black	Straight / Beaded	A/Z/C	2.500/10.000	500/750	7-12	APC 1	8.4 cal/cm²
24-9022*	14" / 36cm	Yellow	Straight / Beaded	A/Z/C	2.500/10.000	500/750	7-12	APC 1	8.4 cal/cm²

### Features & Benefits

- Made from 100% natural high grade rubber latex
- Smooth chlorinated surface finish and rolled cuff edge aid donning and doffing
- Environmentally friendly dipping process free from the use of solvents
- Ergonomic design and finger shape minimises hand fatigue
- Increased flexibility in cold environments
- Silicone-free
- Double certification EN 60903 and ASTM D120

AC = Alternative Current (Flows both ways)

DC = Direct Current (Flows one way)

\*Stocked

\*\*Including half sizes

### EN Category description

- A - Acid
- Z - Ozone
- C - Extreme low temperature

### Certification



Manufactured and tested in accordance with IEC 60903, EN 60903 and ASTM D120.

CE 0598

### Packaging

1 pair p/polybag and individual box.  
10 pairs p/carton

