



# STEP SAVING VALVES FOR THE PROFESSIONAL

**NEW WEBSTONE SOLUTIONS SIMPLIFY FUTURE SERVICE**



PATENTS PENDING

## NEW PRO-PAL ADD-A-DRAIN™

- Add a hose connection to appliances or the end of any line
- Full-port, quarter-turn alternative to traditional boiler drains
- Straight design for more convenient service access
- Compact handle saves space
- Lead-free forged DZR brass suitable for hydronic or potable applications
- Connections up to 1 1/2" cover a broad range of applications




**PRO-PAL ADD-A-DRAIN**  
Full Port Forged DZR Brass Ball Valve, w/ Cap & Strap & Adjustable Packing Gland

**LEAD-FREE BRASS**  
Certified to NSF/ANSI 61 & 372

SIZE	ITEM#	CTN/CASE	CASE WT
<b>MIP × Hose</b>			
1/2" × 3/4"	H-20302W	12/72	31
3/4" × 3/4"	H-20303W	12/72	36
1" × 3/4"	H-20304W	8/64	39
1 1/4" × 3/4"	H-20305W	6/48	33
1 1/2" × 3/4"	H-20306W	6/36	36
<b>FIP × Hose</b>			
1/2" × 3/4"	H-40302W	12/72	31
3/4" × 3/4"	H-40303W	12/72	33
1" × 3/4"	H-40304W	8/64	36
1 1/4" × 3/4"	H-40305W	6/48	38
1 1/2" × 3/4"	H-40306W	6/36	34
<b>SWT × Hose</b>			
1/2" × 3/4"	H-50302W	12/72	27
3/4" × 3/4"	H-50303W	12/72	31
1" × 3/4"	H-50304W	8/64	31
1 1/4" × 3/4"	H-50305W	6/48	36
1 1/2" × 3/4"	H-50306W	6/36	33
<b>Press × Hose</b>			
1/2" × 3/4"	H-80302W	12/72	33
3/4" × 3/4"	H-80303W	12/72	38
1" × 3/4"	H-80304W	8/64	37
1 1/4" × 3/4"	H-80305W	6/48	38
1 1/2" × 3/4"	H-80306W	6/36	38

**Customize Your Installation**  
G-Thread model compatible with a host of fittings and accessories



**PRO-PAL ADD-A-DRAIN**  
Full Port Forged DZR Brass Ball Valve, w/ Cap & Strap & Adjustable Packing Gland · Requires (1) G-Union Fitting (Sold Separately)

**LEAD-FREE BRASS**  
Certified to NSF/ANSI 61 & 372

SIZE	ITEM#	CTN/CASE	CASE WT
<b>G-Thread × Hose</b>			
1" × 3/4"	H-G0304W	8/64	36
1 1/2" × 3/4"	H-G0306W	6/36	34

**Webstone**®  
a brand of **NIBCO**®

**VALVE INNOVATION**  
**INSTALLATION SOLUTIONS**

webstonevalves.com/propal



**WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov

LEAD-FREE: Weighted average lead content ≤ 0.25%

# G-UNION ACCESSORIES

- Match the G-Thread size with the accessory/fitting G-Union size
- Multiple options to customize your installation
- Reversible check inserts for maximum versatility



## BALL VALVE W/HOSE END

- Ideal for heavy-duty applications

**FULL PORT FORGED BRASS BALL VALVE**  
w/ Cap & Strap, Reversible Handle & Adjustable Packing Gland

**LEAD-FREE BRASS**

Certified to NSF/ANSI 61

SIZE	ITEM#	CTN/CASE	CASE WT
<b>FIP x Hose</b>			
1/2" x 3/4"	H-40312W	10/60	30
3/4" x 3/4"	H-40313W	10/60	42
<b>SWT x Hose</b>			
1/2" x 3/4"	H-50312W	10/100	49
3/4" x 3/4"	H-50313W	10/60	42

**LEAD-FREE BRASS**

Certified to NSF/ANSI 61 & 372

SIZE	ITEM#	CTN/CASE	CASE WT
<b>Press x Hose</b>			
1/2" x 3/4"	H-80312W	5/50	29
3/4" x 3/4"	H-80313W	5/40	33

G-UNION SIZE	SYSTEM PIPING	FIP	MIP	SWT	Press	Push	F1960 PEX	F1807 PEX
<b>Forged DZR Brass Fitting</b>								
1"	1/2"	H-7-2102W WP	H-7-4102W WP	H-7-5102W WP	H-7-8102W WP	H-7-6102W WP	H-7-3102W WP	H-7-1102W WP
1"	3/4"	H-7-2103W WP	H-7-4103W WP	H-7-5103W WP	H-7-8103W WP	H-7-6103W WP	H-7-3103W WP	H-7-1103W WP
1"	1"	H-7-2104W WP	H-7-4104W WP	H-7-5104W WP	H-7-8104W WP	-	H-7-3104W WP	H-7-1104W WP
1 1/2"	1 1/4"	H-7-2165W WP	H-7-4165W WP	H-7-5165W WP	H-7-8165W WP	-	-	-
1 1/2"	1 1/2"	H-7-2166W WP	H-7-4166W WP	H-7-5166W WP	H-7-8166W WP	-	-	-
<b>Forged DZR Brass Fitting with Integral Check Valve</b>								
1"	1/2"	H-7-2202W WP	H-7-4202W WP	H-7-5202W WP	H-7-8202W WP	H-7-6202W WP	H-7-3202W WP	H-7-1202W WP
1"	3/4"	H-7-2203W WP	H-7-4203W WP	H-7-5203W WP	H-7-8203W WP	H-7-6203W WP	H-7-3203W WP	H-7-1203W WP
1"	1"	H-7-2204W WP	H-7-4204W WP	H-7-5204W WP	H-7-8204W WP	-	H-7-3204W WP	H-7-1204W WP

**G-UNION ELBOW**  
Forged DZR Brass Fitting

**LEAD-FREE BRASS**  
Certified to NSF/ANSI 61 & 372

SIZE	ITEM#	CTN/CASE
G-Union x G-Thread		150 PSI CWP Max
1"	H-7-G144W-A	10/60



**DUAL SCALE TEMPERATURE GAUGE**  
w/ Integrated Forged Brass Fitting - 1 1/2" Dial  
Temperature Range 32° - 248°F

**LEAD-FREE BRASS**

Certified to NSF/ANSI 61 & 372

SIZE	ITEM#	CTN/CASE
G-Union x G-Thread		
1"	H-32000W	10/100



## IDEAL FOR USE WITH ADD-A-GAUGE TO ANY STANDARD HOSE CONNECTION IN JUST MINUTES

PATENTED TECHNOLOGY

- Utilize any hose connection as a gauge port
- Suitable for temporary or permanent gauge installation
- Works with temperature and/or pressure gauges



**PRO-PAL ADD-A-GAUGE**  
Forged Brass Hose Fitting w/ 1/8" Bleeder (Capped)

**LEAD-FREE BRASS**

SIZE	ITEM#	CTN/CASE	CASE WT
<b>FOR CONNECTION TO PRESSURE GAUGE</b>			
Hose x FIP Union		250 PSI CWP Max/250°F Max	
3/4" x 1/4"	H-30000W-P	10/100	27
<b>FOR CONNECTION TO TEMPERATURE/PRESSURE GAUGE</b>			
Hose x FIP Union		250 PSI CWP Max/250°F Max	
3/4" x 1/2"	H-30000W-TP	10/100	27