### Bit-Checks / Bit-Safes BiTorsion





















**EAN:** 4013288179869 **Size:** 69x65x20 mm

Part number:05057420001Weight:105 gArticle number:Bit-Check 12 BiTorsion 1Country of origin:CZ

Customs tariff 82079030 number:

- Upright positionable, multi-component Bit-Check
- Rapidaptor holder for rapid bit change
- BiTorsion bits for long service life
- Tough viscous bits for universal use
- Take it easy tool finder: colour coding according to profile and size

Tough-absorbing bits for universal use. BiTorsion bits with an elastic torsion zone - where kinetic energy is diverted from peak loads - and softer BiTorsion zone to prevent the bit tip from twisting under high strain. This greatly extends the product service life. Offer the best possible service life with the appropriate holder. Comes with Rapidaptor technology, which allows bits to be attached without any need to actuate the sleeve. The removal of the bit is simple, just by pushing the sleeve forward - for rapid bit change with just one hand. For the take-up of bits with 1/4" hexagon head drive as per DIN ISO 1173-C 6.3 und E 6.3. For insertion in the power screwdriver or into the chuck of the power drill. The multi-component Bit-Check is convincing on account of its low weight and the maximum possible degree of compactness. In this respect, the soft material in the lower section of the Bit-Check ensures that the bits are securely held whilst being simple to remove at the same time. The profile and size of the bits are easy to recognise thanks to the Wera "Take it easy" Tool Finder with its colour coding and clearly visible imprint.

### Bit-Checks / Bit-Safes BiTorsion



## At the workplace

## **BiTorsion Bits**

## Rapidaptor holder

### Chuck-all



The Bit-Checks can be positioned upright at the workplace so the tool is always quickly to hand.



BiTorsion bits are absolutely premium products. They have a softer BiTorsion zone which reduces the hardness of the shaft by about 20 % in comparison to the drive tip. This means that the peak loads that cause bit breakage and premature wear are absorbed in this zone - something which enhances the service life of the bits.



Rapid bit change without needing any additional tools. One-hand operation with a freely spinning sleeve for simplified guidance of the tool.



The Rapidaptor quick-release chucks hold ¼" DIN ISO 1173-C 6,3 and E 6,3 as well as Wera series 1 and 4 bits.

### Rapid-in and self-lock



The bit can be pushed into the adaptor without moving the sleeve. The lock is activated automatically as soon as the bit is applied to the screw. Bits are held securely and wobble-free.

# Rapid-out



Simply push the sleeve forward to change the bit. The spring mechanism lifts the bit off the magnet and unlocks the tool. The bit can be easily removed. The rapid-out function makes it easy to remove even the smallest bits without extra tools.

# Single-hand function



Every function of the Rapidator quick-release chuck, such as inserting or releasing bits, can be carried out with one hand. This is faster, more economical and more ergonomic. There are no unnecessary manoeuvres.

# "Take it easy" tool finder system



The "Take it easy" Bit-Checks have bits with a sleeve which - from its colour (e.g. red = Phillips) and size designation - make it simple to access the right bit quickly.

Web link

https://products.wera.de/en/bits\_holders\_adaptors\_and\_sets\_bit\_sets\_bit-checks\_\_bit-safes\_bitorsion\_bit-check\_12\_bitorsion\_1.html

# Bit-Check 12 BiTorsion 1, 12 pieces

### Bit-Checks / Bit-Safes BiTorsion



## Set contents:

# 889/4/1 K Rapidaptor Universal Bit Holder, 1/4" x 50 mm $\,$

05052502001 1x 1/4" x 50 mm



## 851/1 BTZ bits, PH 1 x 25 mm

<b>O</b>	05056420001	1x	PH 1 x 25 mm
// Wera	05056422001	2x	PH 2 x 25 mm

### 855/1 BTZ bits, PZ 1 x 25 mm

<b>*</b>	05056720001 05056722001	 PZ 1 x 25 mm PZ 2 x 25 mm
M Wera		

# 867/1 BTZ TORX® bits, TX 10 x 25 mm

out i biz folike bits,	IN TO A ZO IIIIII		
	05066120001	1x	TX 10 x 25 mm
W Wera	05066122001	1x	TX 15 x 25 mm
	05066124001	1x	TX 20 x 25 mm
	05066126001	1x	TX 25 x 25 mm
	05066128001	1x	TX 30 x 25 mm