

DARK



MORE INFO >>



MORE INFO >>

		CCT	Beam	LOR
DARK	A274-00-10- NX N	2700K	19°	80%
	A274-00-11- NX N	3000K	19°	80%
	A274-00-12- NX N	4000K	19°	80%
	A274-00-20- NX N	2700K	40°	83%
	A274-00-21- NX N	3000K	40°	83%
	A274-00-22- NX N	4000K	40°	83%



IP67 | IK08 | CRI>90 | L90B10 >102,000h



		CCT	Beam	LOR
DARK Honeycomb	A513-00-10- NX N	2700K	17°	54%
	A513-00-11- NX N	3000K	17°	54%
	A513-00-12- NX N	4000K	17°	54%
	A513-00-20- NX N	2700K	30°	53%
	A513-00-21- NX N	3000K	30°	53%
	A513-00-22- NX N	4000K	30°	53%



IP67 | IK08 | CRI>90 | L90B10 >102,000h



*DRIVER OPTIONS	P	I	CCT	Flux
0434-00-39 1 to 12 Darks	1W	350mA	2700K	100 lm
			3000K	120 lm
			4000K	130 lm
NO DIM IP20				
0434-00-40 1 to 12 Darks	2,1W	700mA	2700K	180 lm
			3000K	200 lm
			4000K	240 lm
NO DIM IP20				
0434-00-41 1 to 11 Darks	3,2W	1050mA	2700K	250 lm
			3000K	280 lm
			4000K	325 lm
NO DIM IP20				


220 V~ | OTHER DIM OPTIONS PLEASE CONSULT

OPTIONAL ACCESSORY



Connector IP67

0434-01-66- | N |



For cable Ø4,5-6,5mm, section <1,5mm²





DARK & DARK HONEYCOMB



DARK M & DARK M HONEYCOMB



DARK M ASYMMETRIC



COLOUR | NX ■ | N ■ |

MATERIAL | INOX AISI 304 | AL | GL-TRANS |

RAL ⓘ >> 312

Ⓜ >> 288



MORE INFO >>



MORE INFO >>



MORE INFO >>

		CCT	LOR
DARK M	A301-00-10- NX N	2700K	75%
	A301-00-11- NX N	3000K	75%
	A301-00-12- NX N	4000K	75%



IP67 | IK08 | CRI>90 | L90B10 >55,000h



		CCT	LOR
DARK M Honeycomb	A514-00-10- NX N	2700K	53%
	A514-00-11- NX N	3000K	53%
	A514-00-12- NX N	4000K	53%



IP67 | IK08 | CRI>90 | L90B10 >55,000h



		CCT	LOR
DARK M Asymmetric	A440-00-10- NX N	2700K	75%
	A440-00-11- NX N	3000K	75%
	A440-00-12- NX N	4000K	75%



IP67 | IK08 | CRI>90 | L90B10 >55,000h



*DRIVER OPTIONS	P	I	CCT	Flux
0434-00-36 1 Dark M	4,6W	140mA	2700K	640 lm
			3000K	665 lm
NO DIM IP20			4000K	675 lm
0434-00-37 1 Dark M	6,7W	200mA	2700K	865 lm
			3000K	900 lm
NO DIM IP20			4000K	915 lm
0434-00-38 1 Dark M	10,5W	300mA	2700K	1220 lm
			3000K	1265 lm
NO DIM IP20			4000K	1290 lm

220 V~ | DRIVER MUST BE PLACED ON REMOTE PHASE CUT & OTHER DIM OPTIONS PLEASE CONSULT


ⓘ >> 282

OPTIONAL ACCESSORY

Connector IP67

0434-01-66- | N |

For cable Ø4,5-6,5mm, section <1,5mm²



COLOUR | NX ■ | N ■ |

MATERIAL | INOX AISI 304 | AL | GL-TRANS |

RAL ⓘ >> 312

Ⓜ >> 288