

KILTER I

6W | 375 lm | 2700K

T30-500-6W-2700K-S14D-FR

Kilter bulb 500mm length 6W 2700K S14D frosted 240V

tala®

The Kilter bulb by Tala is a new take on an architectural lighting staple. Defined by its tubular shape, Kilter achieves consistent light throw and reduce shadowed endpoints while offering Tala's signature dimming characteristics.



PHYSICAL

Bulb diameter:	30mm
Bulb length:	500mm
Glass shape:	T30
Base:	S14D
Materials:	Glass & nickel
Glass finish:	Frosted
Weight:	185g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54

ELECTRICAL

Power:	6W
Current:	0.03A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	63
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2700K
Lumens:	375 lm
Incandescent equiv.:	32W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	75
TM30 - Rg	95
TM30 - Rf	92

IES/LDT photometry files
and product photography
available on request



DIMMING

Dimmable 0-100%
Recommended dimmer: Varilight V-Pro
(For a full list of recommended and
compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40
Nieuwegein 3437 JN

LOGISTICAL

Unit Packaging
PC/Ctn: 1
Gross weight: 350g
L 560 x W 70 x H 70mm

Outer Carton
PC/Ctn: 4
Gross weight: 1.7kg
L 565 x W 290 x H 75cm

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights

WARRANTY

2 years

EAN

5060915712103