

KILTER WALL LIGHT

tala®

SKU: KLT-WL-SB-01-EU

FINISH: POLISHED BRASS

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular solid brass fixture is designed to house Tala's Kilter S14d light sources. IP44 rated for outdoor use.




PHYSICAL

Sconce:	L55 x W107 x H107mm
Not used:	L- x W- x H-mm
Cable length:	-
Materials:	Brass
Finish:	Polished Brass
Weight:	1200g
IP rating:	IP44
Base:	S14D

ELECTRICAL

Appliance class:	Class I
Power:	6W MAX
Voltage:	220-240V~
Frequency:	50/60Hz



DIMMING

Recommended dimmer: Varilight V-Pro
Included Dimmer: N/A
(For a full list of recommended and compatible dimmers see website)

LOGISTICAL

Unit Packaging
PC/Ctn: 1
Gross weight: 1360 g
L 150 x W 150 x H 90mm

WARRANTY

2 years

EAN

5060915713476

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40
Nieuwegein 3437 JN

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

KILTER WALL LIGHT

tala®

SKU: KLT-WL-DG-01-EU

FINISH: DARK GREY

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular aluminium shell is designed to house Tala's Kilter S14d light sources. IP44 rated for outdoor use.




PHYSICAL

Sconce:	L55 x W107 x H107mm
Not used:	L- x W- x H-mm
Cable length:	-
Materials:	Powder coated aluminium
Finish:	Dark Grey
Weight:	480g
IP rating:	IP44
Base:	S14D

ELECTRICAL

Appliance class:	Class I
Power:	6W MAX
Voltage:	220-240V~
Frequency:	50/60Hz



DIMMING

Recommended dimmer: Varilight V-Pro
Included Dimmer: N/A
(For a full list of recommended and compatible dimmers see website)

LOGISTICAL

Unit Packaging
PC/Ctn: 1
Gross weight: 680 g
L 150 x W 150 x H 90mm

WARRANTY

2 years

EAN

5060915712172

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40
Nieuwegein 3437 JN

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

KILTER WALL LIGHT

tala®

SKU: KLT-WL-WT-01-EU

FINISH: WHITE

The Kilter Wall Light by Tala mounts flush to the wall or ceiling to create a seamless exchange with the environment. The circular aluminium shell is designed to house Tala's Kilter S14d light sources. IP44 rated for outdoor use.




PHYSICAL

Sconce:	L55 x W107 x H107mm
Not used:	L- x W- x H-mm
Cable length:	-
Materials:	Powder coated aluminium
Finish:	White
Weight:	480g
IP rating:	IP44
Base:	S14D

ELECTRICAL

Appliance class:	Class I
Power:	6W MAX
Voltage:	220-240V~
Frequency:	50/60Hz



DIMMING

Recommended dimmer: Varilight V-Pro
Included Dimmer: N/A
(For a full list of recommended and compatible dimmers see website)

LOGISTICAL

Unit Packaging
PC/Ctn: 1
Gross weight: 680 g
L 150 x W 150 x H 90mm

WARRANTY

2 years

EAN

5060915712165

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40
Nieuwegein 3437 JN

tala.co.uk | hello@tala.co.uk | +44 7700 170343

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights