

HEALTHY BUILDINGS KNOW WHEN TO CLEAN AIR

Better indoor air quality starts with precise detection and monitoring.

IAQ Sensors Sell Sheet

Due to COVID-19, 51% of workers say fear of getting sick at work is a barrier to returning.¹

Honeywell

IAQ SENSORS FOR HEALTHY BUILDINGS

Honeywell Healthy Buildings help keep facilities safer for occupants, in part by cleaning the air automatically as people come and go. To do that, your building needs accurate data about the air quality – and that starts with our versatile range of sensors for indoor air quality (IAQ).

INDOOR AIR QUALITY REINFORCES BUILDING HEALTH

Studies show that comfort levels inside your building can impact occupant health, satisfaction, and productivity.² This is influenced by factors such as temperature and humidity, as well as air that is free of irritants, allergens, and unwelcome odors.

REASSURE OCCUPANTS THAT YOUR BUILDING IS MEASURABLY SAFER

Proper air cleaning and exchange can help reduce disease transmission by removing or dispelling pathogens, as well as odors, chemicals, and CO₂. A relative humidity of 40–60% can also decrease exposure to infectious particles and reduce virus transmission.



MULTI-SENSOR

Our multi-sensing devices report a full range of air quality factors to your building management system (BMS) for automated air cleaning and IAQ alerts.

- Temperature, humidity, CO₂, PM 2.5, and TVOC
- Duct and wall-mounted sensors

TOTAL VOLATILE ORGANIC COMPOUNDS (TVOC)

Detect poor air quality due to a range of VOCs – such as odors, bioeffluents, and outdoor pollutants.

- VOC concentrations can be 10 times higher indoors
- Duct and wall-mounted sensors

FINE PARTICULATE MATTER

Track levels of irritating fine particulate matter that contribute to asthma or other respiratory diseases.

- Choose from a range of detection levels (PM_{1.0}, PM, PM_{4.0}, or PM₁₀)
- Wall-mounted room sensor

CARBON DIOXIDE

CO₂ sensing is a proven way to gauge occupant density and automate demand-controlled ventilation (DCV), optimizing both air quality and energy use.

- Factory-certified, self-calibrating sensors
- Wall-mounted room sensor

Material Number	Sensor Type	Mounting	Output	Display
C7355A1050	Temp/Hum/CO ₂ /TVOC/PM	Wall	MODBUS RTU	No
C7355B1052	Temp/Hum/CO ₂ /TVOC/PM	Duct	MODBUS RTU	No
C7364A1016	TVOC	Wall	4-20mA, 0-5/10VDC, 3-step	No
C7364B1014	TVOC	Duct	4-20mA, 0-5/10VDC, 3-step	No
C7363A1017	PM	Wall	0-5/10VDC	No
C7232A1008/U	CO ₂	Wall	2-10VDC, 0/4-20MA	Yes
C7232B1006/U	CO ₂	Duct	2-10VDC, 0/4-20MA	Yes
C7232A1016/U	CO ₂	Wall	2-10VDC, 0/4-20MA	No
C7632B1002/U	CO ₂	Duct	0-10VDC (fixed)	No
C7262A1016/U	CO ₂	Wall	0/2-10VDC, 0/4-20MA	No
C7262A1008/U	CO ₂	Wall	2-10VDC, 0/4-20MA	Yes
C7232B1014/U	CO ₂	Duct	0/2-10VDC, ww0/4-20MA	No

¹ PWC Americas. [Reboot: Employees want safety and well-being prioritized](#) [Accessed September 24, 2020]

² U.S. Department of Energy, Energy Efficiency and Renewable Energy. [Building Science Introduction - Airflow](#). [Accessed October 6, 2020]

³ Harvard Medical School. [Optimize Occupant Health, Building Energy Performance and your Revenue Through Indoor-Air Hydration](#). Dr. Stephanie Taylor, M.D., M. Arch

Honeywell Building Technologies

715 Peachtree St NE
Atlanta, Georgia 30308
honeywell.com

01-00201 | 10/20
© 2020 All Rights Reserved Honeywell Inc.

Honeywell