

TP9600 Series Pneumatic Thermostats

SPECIFICATION DATA



FEATURES

- Bimetal sensing element
- High capacity
- Straight-scale thermometer located on thermostat rather than on cover
- Plug-in air connections
- Adjustable throttling range
- Replaceable filter
- Contemporary, styled cover

APPLICATION

TP9600 Series Pneumatic Thermostats provide high-capacity, proportional control of pneumatic devices, such as valves and damper actuators, in heating, ventilating, and air conditioning systems. These two-pipe, pilot-bleed Thermostats maintain comfortable conditions and are designed for trouble-free service. Covers are provided with all models.



DESCRIPTION

TP9600 Series Pneumatic Thermostats provide high-capacity, proportional control of pneumatic devices, such as valves and damper actuators, in heating, ventilating, and air conditioning systems. These two-pipe, pilot-bleed Thermostats maintain comfortable conditions and are designed for trouble-free service. Covers are provided with all models.

SPECIFICATIONS

Models:

- TP9600A: Direct acting; cover: setpoint visible and adjustable; thermometer visible
- TP9600B: Reverse acting; cover: setpoint visible and adjustable; thermometer visible
- TP9603A: Direct acting; cover: setpoint concealed and thermometer concealed
- TP9603B: Reverse acting; cover: setpoint concealed and thermometer concealed

Setpoint Range:

60° to 90°F (15° to 30°C)

Throttling Range:

Adjustable: 2° to 10°F (1° to 5°C)

Filter:

Replaceable cartridge type

Maximum Safe Air Pressure:

25 psi (172 kPa)

Maximum Safe Temperature:

150°F (66°C)

Setpoint Adjustment:

Knob with adjustable, locking stops for minimum and maximum settings

Thermometer:

Spiral bimetal

Mounting:

Wall mounted
Horizontal or vertical

Branch Line Indication:

Self-sealing gage tap accessible under cover

Air Consumption:

0.011 scfm (5.19 ml/s)

Dimensions (Cover):

3-1/4 in. (83 mm) high x 2 in. (52 mm) wide x 1-5/8 in. (41 mm) deep

Covers:

Locking type

Fittings:

Order separately (see 95-5597)

Accessories:

See 77-1003

By using this Honeywell literature, you agree that Honeywell will have no liability for any damages arising out of your use or modification to, the literature. You will defend and indemnify Honeywell, its affiliates and subsidiaries, from and against any liability, cost, or damages, including attorneys' fees, arising out of, or resulting from, any modification to the literature by you.

Home and Building Control

Honeywell Inc.
Honeywell Plaza
P.O. Box 524
Minneapolis MN 55408-0524

Honeywell Latin American Division

Miami Lakes Headquarters
14505 Commerce Way Suite 500
Miami Lakes FL 33016

Home and Building Control

Honeywell Limited-Honeywell Limitée
155 Gordon Baker Road
North York, Ontario
M2H 2C9

Honeywell Europe S.A.

3 Avenue du Bourget
B-1140 Brussels Belgium

Honeywell Asia Pacific Inc.

Room 3213-3225
Sun Hung Kai Centre
No. 30 Harbour Road
Wanchai
Hong Kong

Honeywell

Helping You Control Your World®

