

## Specifications

Product Line	Metropolitan Collection XL
Product Type	Stone Polymer Composite
Core Material	Rigid Polymeric Core
Wear Layer	22mil
Overall Thickness	7.0mm
Nominal Plank Size	9" x 60"
Actual Plank Size	230 mm x 1524 mm
Edge Profile	Painted Bevel
Embossing	Natural Wood Texture
Finish	DiamondDust Coating
Installation Type	Floating   Uniclic
Attached Pad	1.0mm IXPE Sound Reducing

## Shipping

### CARTON

Planks	5
Square Feet	18.86
Weight (lbs)	49.4
Square Meters	1.752
Weight (kg)	22.5

### PALLET

Cartons	56
Square Feet	1,056.16
Weight (lbs)	2,821
Square Meters	98.12
Weight (kg)	1,282

### CONTAINER

Cartons	1,176
Square Feet	22,179.36
Weight (lbs)	59,241
Square Meters	2,060.51
Weight (kg)	26,928

## Warranty



**30 YEAR  
 RESIDENTIAL**



**15 YEAR  
 COMMERCIAL**



WATERPROOF  
 MATERIAL



UNIQUE PLANK  
 PATTERN VARIATION



SCRATCH &  
 STAIN RESISTANT

## Performance Testing

Slip Resistance	DIN 51130:2014   EN13893	R9   Class DS
Scratch Resistance	ISO 1518:2019 (Stylus C)	Not Damaged With Weights $\geq 20$ N
Static Load	ASTM F970 / ASTM F387	Commercial: $\leq 0.13$ mm
Castor Chair	EN 426	$\geq 11,000$ Cycles
Dimensional Stability (80°C -6h)	ISO 23999/ ASTM F2199	$\leq 0.1\%$
Curl (80° -6h)	ISO 23999/ ASTM F2199	$\pm 2$ mm
Light Resistance	ASTM F1515	$\Delta E \leq 8$
Heat Resistance	ASTM F1514	$\Delta E \leq 8$
Fire Resistance and Smoke Emission	EN ISO 9239-1	Class Bfl s1
Chemical Resistance	ASTM F925	PASS
Phthalate Content	CPSC-CH-C1001-09.3	Not Detected
Heavy Metals	ASTM F963	PASS
VOC Emission	BS ISO 16000 / ASTM D5116	Certified FloorScore & GreenGuard Gold
Vinyl Chloride Monomer (VCM) Content	ASTM D4443-95(2002)	Not Detected
Suitable For Underfloor Heating	-	YES   27°C Max

## Sound Testing

Impact Sound Insulation Class (IIC)	63
Sound Transmission Class (STC)	62