HYDRO-CORE ® THE CORE OF ANY PROFESSIONAL HYDRONIC INSTALLATION


NEW FULLY INTEGRATED COMPACT BODY

The Hydro-Core Manifold is the ideal solution for near boiler piping or secondary loops.

- NEW Integrated all-press design saves even more space and eliminates leak paths
- Eliminates costly field fabrication
- Avoids precise calculations
- Simplifies future maintenance
- All with EXPERT looking results

WORK SMARTER





ARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov

PRECISION-CRAFTED CLOSELY SPACED TEES For hydraulic separation

3


T-FLOW BALL Directs flow into either the boiler

or purge drain

PATENTED TECHNOLOGY

HYDRO-CORE MANIFOLD Closely Spaced Tees w/ (2) Full Port Ball Valves, Hi-Flow Hose Drains & Adjustable Packing Glands

		STANDARD BRASS					
SIZE	ITEM#	CTN/CASE	CASEWT				
Press Run ×	Press Valve	2	50 PSI CWP Max				
1"×3/4"	H-88343-2	1/6	27				
1"×1"	H-88344-2	1/6	32				
1 1/4" × 1"	H-88354-2	1/6	33				
<u>1 1/4" × 1 1/4</u>	" Н-88355-2	1/6	44				



Webstone a brand of **NIBCO**[®]



webstonevalves.com/hydrocore

Webstone

Wabstona

in. f 🔿 🔽



MANIFOLD W/UNION CONNECTIONS

Flexible, customizable design combines your choice of union and flange connections to accommodate different installation needs.

	Manifol Desigr		System Run	Boiler Connection	FIP	SWT	Press × FIP	
		Double Ball Drain	1 1/4"	3/4"	H-48354-43	H-58354-53	H-88354-43	
and and and			1 1/4"	1"	H-48354-44	H-58354-54	H-88354-44	
		Flange Right	1 1/4"	3/4"	H-48754-43	H-58754-53	H-88754-43	0
-			1 1/4"	1"	H-48754-44	H-58754-54	H-88754-44	
33			1 1/2"	1 1/4"	H-48765-45	H-58765-55	H-88765-45	
			1 1/4"	3/4"	H-48854-43	H-58854-53	H-88854-43	
		Flange Left	1 1/4"	1"	H-48854-44	H-58854-54	H-88854-44	
		1 1/2"	1 1/4"	H-48865-45	H-58865-55	H-88865-45		



UNION CONNECTIONS Three distinct styles, see webstonevavles.com for full selection

COMPLETE NEAR BOILER PIPING KITS

A fully-fabricated solution, kits include everything necessary for a successful installation.

- Choice of Press, FIP or SWT Hydro-Core Manifold
- Integrated connections for your specific boiler
- Assembled with copper or flexible stainless steel tubing
- Insulated manifold, supply & return lines

FIND THE RIGHT KIT FOR YOUR BOILER: See webstonevalves.com/ hydrocore for a full boiler compatibility chart

FULLY-INSULATED BODY Custom-fit foam insulation maximizes system efficiency



Complete Near Boiler Piping Kits								
SYSTEM PIPING	ITEM#	ITEM#	ITEM#	ITEM#				
FIP	H-4CC4-NBHK	H-4FK4-WIF	H-4CCL54-54Y	H-4FK5-CH				
SWT	H-5CC4-NBHK	H-5FK4-WIF	H-5CCL54-54Y	H-5FK5-CH				
PRESS	H-8CC4-NBHK	H-8FK4-WIF	H-8CCL54-54Y	H-8FK5-CH				
Kit Features								
SYSTEM RUN	1 1/4"	1 1/4"	1 1/4"	1 1/4"				
BOILER CONNECTION	1"	1"	1"	1"				
MANIFOLD TYPE	Double Ball Drain	Double Ball Drain	Flange Left	Double Ball Drain				
SUPPLY & RETURN PIPING	Bent Copper	Flexible Stainless Steel (Two 12" Lengths)	Bent Copper	Flexible Stainless Steel (10.5" & 12" Lengths)				
FULLY INSULATED	✓	1	✓	✓				
1/4" NPT GAUGE PORT	-	-	-	✓				
PRESSURE GAUGE	-	-	-	 Image: A second s				
3/4" FIP DEVICE PORTS	-	-	\checkmark	1				
MESH "Y" STRAINER	-	-	1	-				
30 PSI BOILER PRV	-	-	-	✓				
3/4" E-X-P E3 DHW SERVICE VALVES	-	-	-	×				
150 PSI DHW PRV		-	-	Lead-Free				

Ð

Webston

LEAD-FREE: Weighted average lead content ≤ 0.25% ©2024 NIBCO INC., All Rights Reserved. FORM#: HC-1124

ć,