

**FULL SLABS:**
**Full Slab Size:** 126" x 63"

**Full Slab Thickness:** 3cm

**Full Slab Weight:** 800 lbs.

**Colors:** Calacatta Oro, Calacatta Super, Super White, Pure White, Giotto, Venezia, Calista, Aurora, Riviera, Raiden, Bedrock, Icelandic, Siesta Key, Fossil, Full Moon, Grey Mist, Sedona, Virelle, Riverrock, Strassa

**SUPER JUMBO SLABS:**
**Super Jumbo Slab Size:** 138" x 79"

**Super Jumbo Slab Thickness:** 3cm

**Super Jumbo Slab Weight:** 1080 lbs.

**Colors:** Fossil, Icelandic, Pure White, Full Moon

| Specifications                                           | Test                               | Result |
|----------------------------------------------------------|------------------------------------|--------|
| Water Absorption                                         | ASTM C97/C97M-18                   | 0.01%  |
| Bulk Specific Gravity                                    | ASTM C97/C97M-18                   | 2.385  |
| Abrasion Resistance (Ha)                                 | ASTM C241/C241M-21                 | 61.3   |
| Thermal Shock Resistance (MPa)                           | EN 14617-6:2012 & EN 14617-2:2016  | 54.8   |
| Mohs' Hardness                                           | EN 101:1991                        | 7      |
| Stain Resistance                                         | IAPMO/ANSI Z124.6-2007 Section 5.2 | PASS   |
| Chemical Resistance                                      | IAPMO/ANSI Z124.6-2007 Section 5.5 | PASS   |
| Compressive Strength Dry (MPa)                           | ASTM C170/C170M-24a                | 198    |
| Compressive Strength Wet (MPa)                           | ASTM C170/C170M-24a                | 203    |
| Flexural Strength Dry (MPa)                              | ASTM C880/C880M-24                 | 56.5   |
| Flexural Strength Wet (MPa)                              | ASTM C880/C880M-24                 | 62.4   |
| Coefficient of Thermal Expansion (x10 <sup>-6</sup> /°C) | ASTM C531-2018                     | 34.0   |