

## Digital Thermometer

Model: DT392, DT392-ES (Spanish)

Easy-to-read front display. Simple one-button operation. ABS sheath can be used as handle extension.



|                          |   |
|--------------------------|---|
| Features                 | One-button operation, on/off switch                         |
| Measurement Range        | -50 to +392°F/-45 to +200°C                                 |
| Unit of Measure          | °F/°C   |
| Accuracy                 | ±2°F  |
| Response Time            | 6-8 second response   |
| On/Off                   | On/off switch   |
| Auto-off                 | Auto-off after 10 minutes                                   |
| Housing Material         | Food-safe ABS   |
| Display Material         | LCD   |
| Display Size             | 0.875 W x 0.375 H (in)/2.2 W x 1.0 H (cm)                   |
| Probe Type               | Thermistor  |
| Probe Material           | 304 stainless steel   |
| Probe Length             | 5"/12.7 cm stem   |
| Probe Diameter           | 3 mm tip  |
| Resolution               | 0.1°F/0.1°C   |
| Casing                   | Sheath  |
| Temperature Guide        | USDA safe food temperature guide on sheath                  |
| Mounting                 | Pocket clip   |
| Operating Range          | 32 to 104°F/0 to 40°C ≤90% RH                               |
| Battery                  | One LR44 alkaline button battery included                   |
| Dimensions               | 1.25 W x 5.625 H x 1.125 D (in)/3.2 W x 14.3 H x 2.9 D (cm) |
| Weight                   | 0.8 oz / 22.7 g (including battery)                         |
| UPC                      | DT392: 0 18436 00609 1, DT392-ES: 0 18436 00712 8           |
| Certification            | NSF <sup>®</sup> Certified, WEEE, CE                        |
| Antimicrobial Protection | BioCote <sup>®</sup>  |
| Warranty                 | 5-Year Limited Warranty                                     |