Eaton JM60030-3MW14

Catalog Number: JM60030-3MW14

Eaton Bussmann series JM modular fuse block, Multi-Wire Load-Side Lug, 30 A, 3-P, 200 kA RMS symmetrical, 120 °C, 50 lb-in Max, Class J, 200 kA RMS symmetrical, Black, Box lug, Both, 200 kAIC, 75 °C, Stranded, DIN rail|Panel, 600 V





Catalog Number

Eaton Bussmann series JM modular fuse JM60030-3MW14

block

UPC

051712620581

Product Length/Depth

Product Height

3.4 in

2.3 in

Product Width

Product Weight

3.3 in

0.475 lb

Warranty

Compliances

Not Applicable

RoHS Compliant

Certifications

ARO

European Pressure Equipment Directive

(PED) 97 /23 EC





Electrical rating

Amperage Rating

30 A

Impulse withstand voltage

200 kA RMS symmetrical

Interrupt rating

200 kAIC

Short-circuit rating

200 kA RMS symmetrical

Torque rating

50 lb-in maximum

Voltage rating

600 V

Physical details

Color

Black

Conductor material rated for

Both

Conductor temperature rating

75 °C

Conductor type

Stranded

Fuse type

Class J

Number of Poles

Three-pole

Operating temperature - max

120 °C

Operating temperature - min

120 °C

General information

Connection

Box lug

Mounting method

DIN rail

Panel

Special features

Multi-Wire Load-Side Lug

Resources

Catalogs

JM60030-3MW14~3POLE J 600V30A PDFB 1-4

Bussmann series complete full line catalog no. 1007

Multimedia

Bussmann series Fuseology

Specifications and datasheets

Eaton Specification Sheet - JM60030-3MW14



Eaton Corporation plc Eaton House 30 Pembroke Road Dublin 4, Ireland Eaton.com

Reserved.

Eaton is a registered trademark.

All other trademarks are © 2023 Eaton. All Rights property of their respective owners.



Eaton.com/socialmedia