

Submittal Data Information LeakBreaker™

Water Heater Shut Off

Job: _____ Engineer: _____ Contractor: _____ Rep: ____

Supersedes: NEW

Features	Applicat	tion		
Re-Settable Testable Quick Connect Wiring Operates on Batteries or Power Supply 2 Color LED Status Light	The Taco I water heat plug desig Componer sensor, valv	LeakBreaker is instal ter, shutting off the yn is specifically eng nts are pre-wired to	water to a leaking v ineered for use on a simplify the installat d/or batteries. LeakBr	g cold water supply to the vater heater. The plumb and a new or retrofit installation. ion process, just plug in the eaker can be tested anytime
Audible Alarm Alarm Mute 2 N/O; N/C Dry Contacts Full Port Valve Easy Removable Actuator	Leak Brea	ker Valve	Water Sensor	Leak Breaker Module
Product Specifications Max. Operating Pressure 140 PSI Max. Shut Off Pressure				
Maximum Ambient Temp 135°F Water Temp		ALL STORE STORES		Hardware Power Cord
Control Panel High Performance Engineered Polym	er LeakB	reaker module operate	s with power cord or 4 A	A batteries (Not Included)
Actuator				
BodyHigh Performance Engineered Polym	er			lel NumberDescription075-H-1LF¾"NPT
GearsHigh Performance Internally Lubricate Engineered Polym	ed i i i i i i i i i i i i i i i i i i i			1-5/8"
Valve				
Body Forged Brass		1/2″		
Stem Brass	4-3/8"			3-3/16"
Press RingBrass				
BallBrass (Chrome Plat	:ed) -	7/8"		
SeatsModified Teflon® O-RingsViton®			1-9/16"-	4"
Approvals	Dime			
(NSF)				

 Taco, Inc., 1160 Cranston Street, Cranston, RI 02920 |
 Tel: (401) 942-8000 |
 FAX: (401) 942-2360

 Taco (Canada), Ltd., 8450 Lawson Road, Suite #3, Milton, Ontario L9T 0J8 |
 Tel: (905) 564-9422 |
 FAX: (905) 564-9436

 Visit our web site: www.TacoComfort.com |
 Printed in USA |
 ©2016 Taco, Inc.

101-178