

Submittal Data Information

UN COMMAND™

EFFECTIVE: July 1, 2013

JOB	ENGINEER	CONTRACTOR	REP
ITEM NO.	MODEL NO.		

Application:

The Taco On Command operates 24 hours to provide hot water "on demand" at the same time it saves water, energy and money.


The On Command is a small, silent pump that you attach to the hot and cold water lines in the cabinet under the most remote kitchen or bath fixture in the home. When the On Command pump is activated, the cool water you normally let run down the drain is recirculated back to the water heater through the cold water line.

On command, the pump circulates the hot water from the water heater and returns the cooled water back through the cold water line. When the hot water arrives at the fixture, the On Command's heat sensor and control board shut off the pump to prevent pumping excess hot water into the cold water line.

NOTE: Standard plumbing and distance requires the On Command to be installed between the hot and cold water line at the most distant hot water location.

Nomenclature:

CT - On Command Threaded USK - Undersink Kit CF - On Command Flanged







RF Wireless Starter Kit





On Command Includes:

On Command Circulator Hard Wire Push Button

- (2) Copper T's
- (2) Flex Hoses

Materials of Construction:

PUMP:

Casing (Volute): Stainless Steel

Stator Housing: Steel

Cartridge: 304 Stainless Steel

Impeller: Noryl Shaft: Ceramic Bearings: Carbon O-Ring: EPDM

INTEGRAL FLOW CHECK (IFC®):

Body, Plunger: Acetal O-Rings: EPDM

On Command Model Numbers										
Product	Connection		Ship							
Number	Sizes	Voltage	RPM	HP	Wgt.					
006-CT	½" Male NPT			1/40	7					
006-CT-USK	½" Male NPT, with Plumbing Kit				8					
008-CT	½" Male NPT	115/60/1		1/25	10					
008-CT-USK	½" Male NPT, with Plumbing Kit		3250	1/25	11					
0011-CF	3/4" Shut-off Flange			1/8	14					
0011-CF-USK	3/4" Shut-off Flange, with Plumbing Kit			1/8	15					

On Command System - Accessories										
Product Number	Description	What It Does								
554-1	Remote Transmitter/ Receiver Kit	To start system with wireless remote control								
554-2	Individual Remote Transmitter	For wireless remote control at multiple locations								
554-3	Individual Starter Button	For hard-wired starter control at multiple locations								
554-4	Motion Sensor Starter Kit	For automatic motion detection start								









101-150

A Taco resource - saving product

Sizing Your On Command Circulator Pump:


STANDARD PIPING - Tank Type Water Heater									
Size of Home	Total Length of Pipe (ft)	Model							
Small	50	006							
Medium	100	800							
Large/Commercial	Over 100	0011							

STANDARD PIPING - Tankless Water Heater								
Size of Home	Total Length of Pipe (ft)	Model						
Small/Medium	< 60	800						
Large/Commercial	> 60	0011						

RECIRCULATION PIPING - Tank Type Water Heater									
Size of Home	Total Length of Pipe (ft)	Model							
Small	100	006							
Medium	200	008							
Large/Commercial	Over 200	0011							


RECIRCULATION PIPING - Tankless Water Heater								
Size of Home	Square Feet	Model						
Small/Medium	< 2500	008						
Large/Commercial	> 2500	0011						


Performance Field Information - 60 Hz




Dimensional and Weight Data:


	MODEL 006-CT												
-	A B		3	С		D		E		F		G	
Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm
6 ⁷ / ₃₂	158	411/16	119	31/2	89	6 ¹⁵ / ₁₆	176	7	178	3 ²¹ / ₃₂	93	5 ²¹ / ₃₂	144







	MODEL 008-CT												
A	A B		С		D		E		F		G		
Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm
61/2	165	45//8	118	4	102	7	178	87/32	209	3 ²¹ / ₃₂	93	5 ²¹ / ₃₂	144





	MODEL 0011-CF												
1	A B (C D		E		F		G				
Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm	Inch	mm
71/2	191	6 ¹ / ₈	156	3 ¹ / ₂	89	7 ⁹ ⁄ ₁₆	192	6 ¹ / ₂	165	4	102	65%	168







Printed in USA