FIVE PENDANT

tala

SKU: CP-WHT-FIV-BP-01-EU FINISH: BRASS



Ē

Ê

Ê

PHYSICAL

Pendant dimension:
Ceiling rose dimension:
Cable length:
Materials:
Finish:
Weight:
IP rating:
Base:

L40mm x W40mm x H79mm L350mm x W350mm x H30mm 3m Powdercoated Steel/Anodised Aluminium White/brass 3750 g IP20 E27

ELECTRICAL

Class I 5 x Max 8 W 220-240 Vac 50/60 Hz




DIMMING	Dimmable 0-100% Recommended dimmer Varilight V-Pro	Tala Energy Ltd. 25b Vyner Street, London, E2 9DG, United Kingdom
WARRANTY	2 years	Tala Europe B.V. Bertus Aafjeshove 40 Nieumwegein 3437 JN
		tala.co.uk hello@tala.co.uk +44 7700 170343
EAN	5060915715920	Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights

FIVE PENDANT

tala

SKU: CP-BLK-FIV-GP-01-EU FINISH: GRAPHITE



Ê

Ê

Ê

Ê

PHYSICAL

- Pendant dimension: Ceiling rose dimension: Cable length: Materials: Finish: Weight: IP rating: Base:
- L40mm x W40mm x H79mm L350mm x W350mm x H30mm 3m Powdercoated Steel/Anodised Aluminium Black/graphite 3750 g IP20 E27

ELECTRICAL

- Appliance class: Power: Voltage: Frequency:
- Class I 5 x Max 8 W 220-240 Vac 50/60 Hz



DIMMING	Dimmable 0-100% Recommended dimmer Varilight V-Pro	Tala Energy Ltd. 25b Vyner Street, London, E2 9DG, United Kingdom
WARRANTY	2 years	Tala Europe B.V. Bertus Aafjeshove 40 Nieumwegein 3437 JN
		tala.co.uk hello@tala.co.uk +44 7700 170343
EAN	5060915715937	Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights


SPHERE V

tala

8W | 720 lm | 2000-2800K SPHR-G200-8W-2000-2800K-E27-MP Sphere G200 8W WoD 2000K to 2800K E27 Matte Porcelain UK/EU LED Bulb


The Sphere V bulb is the largest light source in the Sphere range. Boasting Dim to Warm technology, a smooth matte white finish and an impressive spherical form, this bulb is the ideal pairing for minimalist light fixtures. Fitted with a standard E27 base cap.





CSI/C180 CSI/C270

IES/LDT photometry files and product photography available on request



PHYSICAL

TM30 - Rf

Dulla di sus star	000
Bulb diameter:	200mm 240mm
Bulb length:	
Glass shape:	G200
Base:	E27
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	250g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54
ELECTRICAL	
Power:	8W
Current:	0.04A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	90 lm/W
Lifetime:	15,000 hrs
ILLUMINATION	
CCT:	2000-2800K
Lumens:	720 lm
Incandescent equiv.:	56W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	90
TM30 - Rg	101

95



DIMMING	Dimmable 0-100% Recommended dimmer: V (For a full list of recomme	U U	Tala Energy Ltd. 25b Vyner Street, London, E2 9DG, United Kingdom
	compatible dimmers see		Tala Europe B.V. Bertus Aafjeshove 40 Nieumwegein 3437 JN
LOGISTICAL	Unit Packaging PC/Ctn: 1	Outer Carton PC/Ctn: 1	tala.co.uk hello@tala.co.uk +44 7700 170343
	Gross weight: 900 L 250 x W 250 x H 400mm	Gross weight: 1.2 L 260 x W 260 x H 410cm	Specification subject to change without notice. Refer to our website for the most
WARRANTY	2 years		recent product documentation. Tala designs in the EU/UK are protected by
EAN	5060400159956		registered and or unregistered design rights