

All-inclusive edge sander.

Edge sanding machine RS-2010.

Your advantages

- Many equipment to fully serve the sanding needs of every carpentry .
- Universal use due to aggregate rotation and power feeder mount
- Fully rotatable, big sanding unit with veneer sanding unit which can be put away in an instant



Technical data

| | |
|---------------------------------|---------------|
| Voltage | 400 V, 50 Hz |
| Power | 3 kW |
| Belt size | 200 x 2760 mm |
| Belt speed | 22 m/sec. |
| Working table dimensions | 450 x 920 mm |

| | |
|---------------------------------|----------------|
| Required space | 1200 x 2000 mm |
| Weight | 500 kg |
| Dust collection diameter | 120 x 80 mm |
| Noise emission | 83 dB(A) |

His highness.

Edge sanding machine R 300.

Your advantages

- Perfect solution for workpiece with up to 300 mm height
- Maximum tool life due to 30 mm of pneumatic oscillation and height adjustable working table.
- Easy belt change due to pneumatic belt tension
- Precise sanding result due to solid grey cast iron plating
- Optionally with other sanding height available



Technical data

| | |
|---------------------------------|--------------------|
| Required space | 1250 × 750 mm |
| Weight | 280 kg |
| Dust collection diameter | Ø 160 mm |
| Oscillation | 30 mm, pneumatisch |
| Required air | 40 l/min |
| Noise emission | 83 dB(A) |

| | |
|---------------------------|---------------|
| Power | 3 kW |
| Belt size | 300 × 2280 mm |
| Belt speed | 11 m/sec. |
| Working table size | 700 × 350 mm |