

AXEON

Calcite Systems

AXEON Calcite Systems use an advanced calcite pH adjusting media in order to meet the most demanding water conditions. These systems are designed for maximum performance with a minimal amount of maintenance and comply with all industry standards and specifications.

AXEON Calcite Systems offer a new dimension in water treatment equipment and have been engineered with both the installer and consumer in mind. Systems are available in many different models and may be customized to fit your application. **AXEON Calcite Systems** can be used in a variety of applications including residential, commercial, industrial and specialty.

AXEON Calcite Systems are effective in correcting pH to reach a non-corrosive equilibrium. All **AXEON Calcite Systems** beds will periodically have to be replenished as the media is depleted. Replenishing is made easy with the quick disconnects built into the In and Out valve.

Standard Features

- Clack 1191 In and Out Valve
- Non-Corrosive UV-Resistant Valve Body
- Structural® Heavy Duty Fiberglass Tank
- Heavy Duty Riser Pipe and Lower Screen

Options and Upgrades

- 90° Extensions and Bypass Valve
- Various Connection Sizes Available
- Stainless Steel Jacket



**Clack
1191**
Front



**Clack
1191**
Back

*With optional
bypass valve and connectors.*

Engineered Water Treatment Solutions

AXEON Calcite Systems

Residential

Product Specifications										
Part Number	Valve	Connections	Media	Tank Size	Cubic Feet	Tank Quantity	Recommended Service Flow	Estimated Peak Flow	Shipping Weight	System Assembled
205552	1191	1" MNPT	Calcite	9 x 48	1	1	1.3–2.6 gpm	12.0 gpm	95 lbs.	Assembled
205553	1191	1" MNPT	Calcite	10 x 54	1.5	1	1.6–3.2 gpm	14.0 gpm	110 lbs.	Assembled

Commercial

Product Specifications										
Part Number	Valve	Connections	Media	Tank Size	Cubic Feet	Tank Quantity	Recommended Service Flow	Estimated Peak Flow	Shipping Weight	System Assembled
205554	1191	1" MNPT	Calcite	12 x 52	2	1	2.4–4.8 gpm	16.0 gpm	150 lbs.	Assembled
205555	1191	1" MNPT	Calcite	13 x 54	2.5	1	2.8–5.6 gpm	17.0 gpm	165 lbs.	Assembled
205556	1191	1" MNPT	Calcite	14 x 65	3	1	3.2–6.4 gpm	18.0 gpm	205 lbs.	Assembled
205557	1191	1" MNPT	Calcite	16 x 65	4	1	4.2–8.4 gpm	20.0 gpm	270 lbs.	Non-Assembled

