

Plastic UV Systems

Disposable models and units with replaceable lamps for economy.



Model PUV-6W with replaceable lamp

Plastic UV systems with replaceable lamps

Model Number	Description	Fitting	Flow Rate	Electrical	Number Per Case
PUV-6W	Complete unit*	1/4" J.G.	1 GPM	6 Watts, 110V, 60 Hz.	25

*Includes ballast

Spare parts

Part Number	Description	Electrical	Number Per Case
PUV-BAL110	Ballast	6 Watts, 110V, 60 Hz.	1
PUV-RL-6W	Lamp	6 Watts, 110V, 60 Hz.	1



Disposable in-line uv systems

Low cost uv systems for residential applications.

Advantages

- Low cost
- Easy installation
- Reliable
- Flow rates from 0.5 to 2.0 GPM

Disposable in-line uv systems

Model Number	Dimensions	Fittings	Flow Rate (GPM)	Electrical	Number Per Case
UV4	2" x 10"	1/4" J.G.	0.5	4 Watts	25
UV6	2-1/2" x 10"	1/4" J.G.	1.0	6 Watts	25
UV8	2-1/2" x 10"	1/4" J.G.	2.0	8 Watts	25
UV24*	2" x 10"	1/4" J.G.	0.5	4 Watts	25
UV26*	2-1/2" x 10"	1/4" J.G.	1.0	6 Watts	25
UV28*	2-1/2" x 10"	1/4" J.G.	2.0	8 Watts	25

Spare parts for disposable in-line uv systems

Part Number	Description	No. / Case
UVBAL120	Ballast (U.S.)	25
UV2BAL*	Ballast (International)	25

*For international electrical requirements.