

Series 150

Reverse Osmosis Controller



Key Features

- 2-line by 20-character, backlit LCD display
- Multi-function keypad
- Visual and audible alarm
- Programable flush modes and setpoints
- Low pressure automatic reset
- Hinged NEMA 4X enclosure
- TDS/Conductivity monitor and sensor
- Permeate monitor and sensor are temperature compensated

Application

The Advantage Controls Series 150 Microprocessor Controller is an ideal solution for the monitoring and control of light commercial reverse osmosis units. This economical controller provides relays for the RO pump, inlet solenoid valve, and membrane flush solenoid valve.

The dry contact switch inputs monitor storage tank level, low and high pressure switch signal, and system lockout for pretreatment backwash or regeneration for on/off operation. All inputs and outputs are controlled with time delays for proper operation.

Build a Model

Model _ - _ _ _ _ _

Base Control Selection

- S150** = Inlet solenoid, flush time delay, pressure switch, and TDS
- S151** = Model 150 with I/O expander for permeate divert or remote alarm relay, plus auxiliary relay with low tank input
- S152** = Model 150 with second TDS board and sensor
- S153** = Model 150 with second TDS board, sensor, and I/O expander

Controller Supply Voltage

- 1** = 120 VAC
- 3** = 120 VAC with UL labeling
- 2** = 220 VAC
- 4** = 220 VAC with UL labeling

Permeate Conductivity Scale

- A** = 0-50 PPM **J** = 0-50 uS
- B** = 0-100 PPM **K** = 0-100 uS
- C** = 0-250 PPM **L** = 0-250 uS
- D** = 0-500 PPM **M** = 0-500 uS
- E** = 0-1,000 PPM **N** = 0-1,000 uS

Second Conductivity Scale

Only available on S152 and S153, use "X" for S150 and S151.

- X** = No conductivity **F** = 0-2,500 PPM
- A** = 0-50 PPM **G** = 0-5,000 PPM
- B** = 0-100 PPM **H** = 0-9,999 PPM
- C** = 0-250 PPM **J** = 0-50 uS
- D** = 0-500 PPM **K** = 0-100 uS
- E** = 0-1,000 PPM **L** = 0-250 uS
- M** = 0-500 uS **N** = 0-1,000 uS
- P** = 0-2,500 uS **Q** = 0-5,000 uS
- R** = 0-9,999 uS

Communications Type

- 0** = None
- 1** = Ethernet communications - Modbus TCP, Ethernet IP
- 2** = Ethernet communications - Bacnet TCP, Ethernet IP

Enclosure

- A** = 8"x6"x4" poly **D** = 14"x12"x8" poly
- B** = 10"x8"x6" poly **E** = 16"x14"x8" poly
- C** = 12"x10"x6" poly **X** = Enclosure defined in Motor Control model number, or no enclosure

Specifications

Power

120-240 VAC, 50/60 Hz, 25 Watts

Environment

-22°F to 140°F, 0-95% RH, noncondensing

Enclosure

8"x6"x4" NEMA 4x

Display:

2 line x 20 character, alphanumeric backlit LCD

Front Panel

Overlay with LCD window, alarm lamp, 7-key membrane switch

Relay Outputs

- RO pump relay 120/240 VAC, 1HP
 - Inlet valve relay 120/240 VAC, 5A
 - Flush valve relay 120/240 VAC, 5A
- Relays supply same output voltage as board power (120 or 240 VAC)

Controls and/or Monitors

- RO high pressure pump motor
- Inlet solenoid valve
- Automatic flush solenoid valve
- Low feed pressure switch
- High pump pressure switch
- RO storage tank level switches (1 or 2)
- Permeate TDS/Conductivity
- Water temperature
- Pre-treatment lockout
- Operating hours

Optional

- Feed TDS/conductivity
- I/O Expander, permeate divert or remote alarm relay and auxiliary relay with tank-low input

Get the Advantage

03/2021

4700 Harold-Abitz Dr
Muskogee, OK 74403
800-743-7431 Phone
888-686-6212 Fax
www.advantagecontrols.com

