



ARE YOU A PRO?

WIFI MADE SIMPLE

PRO

SIMPLE.  
AFFORDABLE.  
PROFESSIONAL.

# A THERMOSTAT COMPANY DESIGNED FOR THE PROFESSIONAL TRADE

500 Series   600 Series   700 Series   800 Series



The industry's simplest private label program just got

# BRIGHTER.

## High Quality

PRO1 thermostats are professional grade, built on proven performance and reliability. It's a difference you can see and feel.

## One Size Thermostats

All PRO1 thermostats have the same size footprint, so you never have to worry about wall marks left by old models. You can also upgrade to new models including WIFI without rewiring using the interchangeable subbase system.


## Full Offering

We offer a full line of thermostats for nearly every application. Whether you need a basic 1 heat, 1 cool non-programmable or a 4 heat, 2 cool WIFI thermostat, PRO1 has you covered.

## Badge System

PRO1 pioneered the free and simple Private Label Program to make your brand the focus. Other companies provide some version of customization, but no other thermostat manufacturer removes their branding altogether. At PRO1, we put YOUR brand front and center, where it should be.

T701i/T721i/T751i



T855iSH



## EXCLUSIVELY FOR PROFESSIONALS



Scan to order your company's private label badges now!

THE POWER OF PARTNERSHIP

www.pro1iaq.com

1-888-PRO1-IAQ (776-1427)

Google Play is a trademark of Google Inc.  
Apple and the Apple logo are trademarks of Apple Inc., registered in the U.S. and other countries. App Store is a service mark



**C** Commercial Time Periods (Occupied/Unoccupied)  
**7D** 7 Day Programmable  
**5/1/1** 5/1/1 Programmable  
**NP** Non-Programmable

Stages of Heat	Stages of Cool	Gas, Electric or Oil	Heat Pump with Auxiliary	Heat Pump without Auxiliary	PTAC Mode	Battery Power	120 Line Voltage	24V Power (Hardwire)	Outdoor Temperature Sensor Compatible	Dual Fuel Compatible	Display Size (Square Inches)	Auto Changeover	Filter Change Reminder	Room Temperature Calibration	Minimum Compressor Run Time	Compressor Short Cycle Delay	Adjustable Heat & Cool Temperature Swing	Cooling Fan Delay	Ventilation Control	Programmable Fan	Pre-Occupancy Fan Purge	IAQ Fan Mode	Always on Display Light	Keypad Lockout	Adjustable Setpoint Limits	Humidity Control	Memory Type (Permanent)	Remote Sensor Capable	Millivolt	ENERGY STAR	Warranty
----------------	----------------	----------------------	--------------------------	-----------------------------	-----------	---------------	------------------	----------------------	---------------------------------------	----------------------	------------------------------	-----------------	------------------------	------------------------------	-----------------------------	------------------------------	--	-------------------	---------------------	------------------	-------------------------	--------------	-------------------------	----------------	----------------------------	------------------	-------------------------	-----------------------	-----------	-------------	----------

Terminals

Accessories

Model	Description	Compatible With
R751WO	Wireless Indoor Remote Sensor	T755WHO PROsync Wireless System
R250W	Wireless Outdoor Remote Sensor	T755WHO PROsync Wireless System
R250S	Wired Outdoor Temperature Sensor	T755S T855SH T855ISH
R251S	Wired Indoor Temperature Sensor	T755S T855SH T855ISH
T150	Stat Guard Cover	Any Thermostat
T119	Universal Wall Plate	Any Thermostat
E219	Weather Resistant Junction Box	Any Thermostat

Model # Nomenclature

<b>Prefix</b>	
T - Thermostats	
R - Remote Sensor	
<b>First Number</b>	
5 - 500 Platform	8 - 800 Platform
6 - 600 Platform	9 - 900 Platform
7 - 700 Platform	
<b>Second Number</b>	
0 - Single Stage	3 - Universal PTAC
1 - Multi Stage Gas	5 - Universal Multi Stage
2 - Multi Stage Heat Pump	7 - Heating or cooling
<b>Third Number</b>	
1 - Non-Programmable	
5 - Programmable	
<b>Suffix</b>	
W - Wireless	S - Wired Remote Sensor
H - Humidity Control	O - Occupancy Sensor
i - Internet Capable	-2 - Series Number
M - Mechanical	L - Line Voltage

	PRØ Model #	7D	NP	C	5/1/1	Stages of Heat	Stages of Cool	Gas, Electric or Oil	Heat Pump with Auxiliary	Heat Pump without Auxiliary	PTAC Mode	Battery Power	120 Line Voltage	24V Power (Hardwire)	Outdoor Temperature Sensor Compatible	Dual Fuel Compatible	Display Size (Square Inches)	Auto Changeover	Filter Change Reminder	Room Temperature Calibration	Minimum Compressor Run Time	Compressor Short Cycle Delay	Adjustable Heat & Cool Temperature Swing	Cooling Fan Delay	Ventilation Control	Programmable Fan	Pre-Occupancy Fan Purge	IAQ Fan Mode	Always on Display Light	Keypad Lockout	Adjustable Setpoint Limits	Humidity Control	Memory Type (Permanent)	Remote Sensor Capable	Millivolt	ENERGY STAR	Warranty	Terminals
WIFI	T855iSH	7D	NP	C		5*	3*										8																			5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, S1, S2, H, D	
	T751i	7D	**			4*	2										7																				5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
	T721i	7D	**			2*	1										7																				5	Rh, Rc, C, Y, W/E, W2, G, O, B
	T701i	7D	**			1	1										7																				5	Rh, Rc, C, Y, W, G, O, B
WIRELESS	T755WHO	7D	5/1/1	NP		4*	2										7																				5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, H, D
	T731WO	NP				2*	1										7																				5	R, C, Y, W, GL, GH, O, B
	T731W	NP				2*	1										7																				5	R, C, Y, W, GL, GH, O, B
BEST	T855SH	7D	5/1/1	NP	C	5*	3*										8																				5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, S1, S2, H, D
	T855	7D	5/1/1	NP	C	4*	2										8																				5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
	T805	7D	5/1/1	NP		1	1										8																				5	Rh, Rc, C, Y, W, G, O, B
BETTER	T755S	7D	5/1/1	NP		4*	2										7																				5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B, S1, S2
	T755	7D	5/1/1	NP		4*	2										7																				5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
	T751	NP				4*	2										7																				5	Rh, Rc, C, Y, Y2, W/E, W2, G, O, B
GOOD	T771	NP				0/1	0/1										4																				5	R, C, W/Y, G
	T731	NP				2*	1										4																				5	R, C, Y, W, GL, GH, O, B
	T725	7D	5/1/1	NP		2*	1										4																				5	R, C, Y, W2, W/E, G, O, B
	T721	NP				2*	1										4																				5	R, C, Y, W2, W/E, G, O, B
	T715	7D	5/1/1	NP		2	2										4																				5	Rh, Rc, C, Y, Y2, W, W2, G, O, B
	T705	7D	5/1/1	NP		1	1										4																				5	Rh, Rc, C, Y, W, G, O, B
	T701	NP					1	1									4																				5	Rh, Rc, C, Y, W, G, O, B
BUILDER	T625-2	7D	5/1/1			2*	1										2																				2	R, C, Y, W/E, W2, G, O, B
	T621-2	NP				2*	1										2																				2	R, C, Y, W/E, W2, G, O, B
	T605-2	7D	5/1/1			1	1										2																				2	Rh, Rc, C, Y, W, G, O, B
	T601-2	NP				1	1										2																				2	Rh, Rc, C, Y, W, G, O, B
MECHANICAL	T501ML4	NP				1	0																														2	4 Wire
	T501ML2	NP				1	0																														2	2 Wire
	T501M	NP				1	1																														2	Rh, Rc, C, Y, W, G, O, B

Stages: 4\* = Two less stages for conventional heat. 2\* = One less stage for conventional heat. Programming\*\* = Can only be modified through the app.

rev. 2405