

# supaferro<sup>®</sup> : SELF-ADHESIVE PLAIN FERRO SHEET (SSF)



## Self-adhesive / ferrous surface for bonding to smooth rigid surfaces

- Manufacturing process: calendered ferro with laminated adhesive
- Material composition: 90% oxidised iron powder, 10% thermo plastic binder, free of PVC & phthalates, laminated one side with double sided adhesive
- Adhesive: acrylic double-sided P.S.A with paper release liner
- Magnetisation: N/A
- Pole pitch: N/A
- Density: 3.6g/cm<sup>3</sup>
- Colour: Dark brown
- Hardness: (Shore-D) 33±5
- Working Face: prepared with a clear sealant
- Magnetic Stability: N/A
- Working Temperature: 10°C to 30°C
- Storage Temperature: 10°C to 35°C
- Compliance: **Supaferro**<sup>®</sup> (SSF) conforms to European toy safety standard, EN71 part 3 & is REACH & RoHS approved
- Packaging: Rolls supplied in cartons (wound on a 3" core). Cut sheets will be in cartons or on pallets

## MORE INFORMATION

[www.anchormagnets.com/pages/supaferro-flexible-iron-media](http://www.anchormagnets.com/pages/supaferro-flexible-iron-media)

### Disclaimer:

Published technical information concerning our products is based upon research, which, to the best of our company's knowledge & belief, is accurate & reliable.

Whilst the guidelines above will assist the purchaser in considering the suitability & performance of the product for each intended use, it remains the user's responsibility to satisfy themselves as to the suitability of such information for each particular use.

Therefore, Anchor Magnets Ltd & Anchor Magnets Europe, accepts no liability in the event of improper use or processing beyond our guidelines.