

supaferro[®] : DRY-WIPE FERRO SHEET (SSF)



Ferrous dry-wipe surface

- Manufacturing process: calendered ferro + laminated vinyl
- Material composition: 90% oxidised iron powder, 10% thermo plastic binder, free of PVC & phthalates, laminated one side with gloss dry-wipe vinyl
- Adhesive: N/A
- Magnetisation: N/A
- Pole pitch: N/A
- Density: 3.6g/cm³
- Colour: white gloss
- Hardness: (Shore-D) 33±5
- Working face: glossy dry wipe
- Magnetic Stability: N/A
- Working temperature: 10°C to 30°C
- Storage temperature: 10°C to 35°C
- Compliance: **supaferro[®]** (SSF) conforms to EN71 part 3 & is REACH & RoHS approved
- Packaging: rolls supplied in cartons (wound on 3" core), cut sheets in cartons or on pallets

MORE INFORMATION

www.anchormagnets.com/pages/supaferro-flexible-iron-media

Disclaimer:

Published technical information concerning our products is based upon research, which, to the best of our company's knowledge & belief, is accurate & reliable.

Whilst the guidelines above will assist the purchaser in considering the suitability & performance of the product for each intended use, it remains the user's responsibility to satisfy themselves as to the suitability of such information for each particular use.

Therefore, Anchor Magnets Ltd & Anchor Magnets Europe, accepts no liability in the event of improper use or processing beyond our guidelines.

supaferro[®] : DRY-WIPE FERRO SHEET (SSF)



Ferrous dry-wipe surface with adhesive

- Manufacturing process: calendered ferro + laminated vinyl + adhesive with filmic liner
- Material composition: 90% oxidised iron powder, 10% thermo plastic binder, free of PVC & phthalates, laminated one side with double sided adhesive (where applicable) & second side with gloss dry-wipe vinyl
- Adhesive: acrylic double sided P.S.A. with filmic release liner
- Magnetisation: N/A
- Pole pitch: N/A
- Density: 3.6g/cm³
- Colour: white
- Hardness: (Shore-D) 33±5
- Working face: glossy dry wipe
- Magnetic Stability: N/A
- Working temperature: 10°C to 30°C
- Storage temperature: 10°C to 35°C
- Compliance: **supaferro[®]** (SSF) conforms to EN71 part 3 & is REACH & RoHS approved
- Packaging: rolls supplied in cartons (wound on 3" core), cut sheets in cartons or on pallets

MORE INFORMATION

www.anchormagnets.com/pages/supaferro-flexible-iron-media

Disclaimer:

Published technical information concerning our products is based upon research, which, to the best of our company's knowledge & belief, is accurate & reliable.

Whilst the guidelines above will assist the purchaser in considering the suitability & performance of the product for each intended use, it remains the user's responsibility to satisfy themselves as to the suitability of such information for each particular use.

Therefore, Anchor Magnets Ltd & Anchor Magnets Europe, accepts no liability in the event of improper use or processing beyond our guidelines.