

G95 - SHORE LED BULB

tala®

6W | 500 lm | 2000-3000K

G95-6W-2000-3000K-E27-MW-230V


Shore WoD 2000K to 3000K E27 Matte Porcelain EU LED Bulb

Tala's G95 for Shore offers highly impressive technical qualities alongside a refined visual aesthetic. A design feature to be celebrated, the bulb is characterised by its Dim to Warm and flicker free behaviour, offering warm and ambient light when dimmed down from 100-0%. Fitted with a standard E27 base cap.




PHYSICAL

Bulb diameter:	95mm
Bulb length:	140mm
Glass shape:	G95
Base:	E27
Materials:	Glass & nickel
Glass finish:	Matte White
Weight:	70g
Max. working temp.:	-5°C to 40°C
IP rating:	IP54



— CIE188
— CIE129

IES/LDT photometry files
and product photography
available on request



ELECTRICAL

Power:	6W
Current:	0.03A
Voltage:	220-240V~
Frequency:	50/60Hz
Power factor:	0.9
Efficiency:	83 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2000-3000K
Lumens:	500 lm
Incandescent equiv.:	45W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	95Ra
R9:	72
TM30 - Rg	100
TM30 - Rf	91



DIMMING

Dimmable 0-100%
Recommended dimmer: Varilight V-Pro
(For a full list of recommended and compatible dimmers see website)

LOGISTICAL

Unit Packaging	Outer Carton
PC/Ctn: 1	PC/Ctn: 10
Gross weight: 125 g	Gross weight: 1.22 kg
L 100 x W 100 x H 145mm	L 520 x W 110 x H 310mm

WARRANTY

2 years

EAN

5060915715449

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40,
Nieuwegein, 3437 JN, Netherlands

tala.co.uk | hello@tala.co.uk | +1 (240) 724-8111

Specification subject to change without
notice. Refer to our website for the most
recent product documentation. Tala
designs in the EU/UK are protected by
registered and or unregistered design rights