

| Item:     |  |
|-----------|--|
| Quantity: |  |
| Project:  |  |

## **Delux Series**

| Models: ☐ ORSU-212 ☐ ORSU-424 ☐ ORSU-636 ☐ ORSU-848 |  |
|---|--|
|---|--|



**ORSU-636** 

# Gas Type: ☐ Natural ☐ LP Elevation (if above 2000 ft.): \_\_\_\_\_

#### Standard Features


- Fully welded frame with lifetime warranty
- 10" high, low profile
- Heavy 3/8" thick plate with 9 3/4" stainless steel wok ring or heavy cast iron 12" x 12" top grates with unique bowl design
- Rear burners elevated 4"
- Full width, removable stainless steel crumb pan for easy cleaning
- Stainless steel sides, front valve cover and ledge for easy cleaning
- Double wall panels for cooler sides
- Cast iron burners rated at 30,000 BTU/hr each featuring removable, non-clog lift off heads with flat top design
- Protected standing pilots for instant ignition
- Manual control for each burner
- Stainless steel tubing for pilots
- 4" high adjustable heavy duty legs included


### **Options and Accessories**














| Model Number | Width (A) | Depth | Number of Burners | Total BTU | Ship Weight |
|--------------|-----------|-------|-------------------|-----------|-------------|
| ORSU-212     | 12"       | 31½"  | 2                 | 60,000    | 82 lbs.     |
| ORSU-424     | 24"       | 31½"  | 4                 | 120,000   | 144 lbs.    |
| ORSU-636     | 36"       | 31½"  | 6                 | 180,000   | 224 lbs.    |
| ORSU-848     | 48"       | 31½"  | 8                 | 240,000   | 292 lbs.    |

#### Notes:

■ Each burner is rated at 30,000 BTU/hr

#### **Gas Connection:**

3/4" NPT on the right hand rear of the appliance.

The pressure regulator (supplied) is to be connected by the installer.

Specify type of gas and altitude, if over 2,000 feet, when ordering.

#### Gas Pressure:

| 5" W.C.  | Natural Gas |
|----------|-------------|
| 10" W.C. | Propane     |

#### Clearances:

|       | Combustible | Non-Combustible |
|-------|-------------|-----------------|
| Rear  | 4"          | 0"              |
| Sides | 15"         | 0"              |

Due to continuing product development to ensure best possible performance, these specifications are subject to change without prior notification.