

## SNL36V100BT SPECIFICATION SHEET



### About Invicta Lithium


The Invicta Lithium 36V range has been specifically designed for replacement of similar size Lead acid batteries. The family is comprised of the popular sizes found in the lead acid range but with the added benefits of Lithium Iron Phosphate (LiFePO4) technology and is ideally suited to deep cycle longer run time applications.

### Features & Benefits

- Large number of cycles >2000 (100% DoD)**  
 Up to 8 times cycle life of SLA lowering your total cost of ownership
- Safe and stable chemistry & Integrated BMS**  
 The use of LiFePO4 along with the integrated BMS ensures protection against over charge / discharge, temperature and short circuit providing the highest degree of safety
- Greater capacity utilisation - 60% more than SLA**  
 Gives longer runtime than equivalent SLA
- High energy density (less than half of the weight of SLA)**  
 Lowering total weight of application
- Fast recharge**  
 Battery is charged and ready to be used sooner
- Flat Discharge Curve**  
 Longer run time & more efficient use of capacity
- Extremely low self-discharge rate**  
 Can sit unused for longer periods of time
- UL1642 at cell level**

Nominal Voltage	38.4V
Nominal Capacity (25°C, 0.33C)	100Ah
Terminal	M8
Length (mm)	520 ± 2mm
Width (mm)	269 ± 2mm
Height (mm)	220 ± 2mm
Weight	37.7kg
Max Charge Voltage	43.8 ± 0.1V
Standby	41.4 ± 0.1V
Cut off Voltage	33.6V
Max. Discharge Current	100A
Recommended Current Discharge	≤ 50A
Max. Pulse Discharge Current (3 Sec)	400A
Max. Charge Current	100A
Recommended Current Charge	≤ 50A
Cycle Life (100% DoD)	≥ 2000
Operating Temp - Charge	0 - 45°C
Operating Temp - Discharge	-20 - 60°C
Short Circuit Release	Load Release
Max. Series / Parallel Configuration	4P
Bluetooth Connectivity	Yes

Terminal M8 Insert



In order to use the Bluetooth functionality, please download our INVICTA App today.




+




## SNL36V100BT SPECIFICATION SHEET


Discharge Curve at Different C Rates




Charging Characteristic (25 °C @ 0.33C)



Cycle Life at Different DoD



Discharge Curve at Different Ambient Temperature (0.33C)



For more information or pricing please contact the team at  
SPB on 1300 001 772 or [sales@spb.net.au](mailto:sales@spb.net.au)