

# FRP-SERIES MEMBRANE HOUSINGS

**AXEON® FRP-Series Membrane Housings** are for continuous long-term use for reverse osmosis, nanofiltration and ultrafiltration elements which are used on typical commercial water treatment systems at pressures up to 300 psi. They feature end entry connections and the True-Lock™ Integrated Locking System, and demonstrate a higher resistance to various climate conditions, feedwater conditions and chemicals.



AXEON 2.5" diameter membrane housings are available in 14", 21" and 40" lengths, and 4.0" diameter membrane housings are offered in 14", 21", 40", and 80" lengths.

## FEATURES

- Fiberglass Construction
- End Entry Connections
- Single Piece ABS End Plugs
- True-Lock™ Integrated Locking System
- High Resistance to Chemicals, such as High Levels of Chlorides and Climate Conditions
- Easy Removable End Plug for Ease of Installation and Maintenance

- Accommodates All Standard Size Membrane Elements
- Adapters, Interconnectors and Mounting Clamps Available

## OPERATING LIMITS

- Maximum Operating Pressure (psi / bar): 300 / 21
- Minimum Operating Temperature (°F / °C): 35 / 2
- Maximum Operating Temperature (°F / °C): 150 / 66

2.5" Series								
Part Number	Model Number	Maximum Pressure (psi)	Number of Membranes	Membrane Diameter (in / mm)	Membrane Length (in / mm)	Feed FNPT (in)	Permeate FNPT (in)	Concentrate FNPT (in)
<b>208421</b>	FRP-2514-300E	300	1	2.50 / 63.50	14.00 / 355.6	1/4	1/4	1/4
<b>208417</b>	FRP-2521-300E	300	1	2.50 / 63.50	21.00 / 533.4	1/4	1/4	1/4
<b>208418</b>	FRP-2540-300E	300	1	2.50 / 63.50	40.00 / 1016	1/4	1/4	1/4

4" Series								
Part Number	Model Number	Maximum Pressure (psi)	Number of Membranes	Membrane Diameter (in / mm)	Membrane Length (in / mm)	Feed FNPT (in)	Permeate FNPT (in)	Concentrate FNPT (in)
<b>208416</b>	FRP-4021-300E	300	1	4.00 / 101.60	21.00 / 533.4	1/2	1/2	1/2
<b>208419</b>	FRP-4040-300E	300	1	4.00 / 101.60	40.00 / 1016	3/4	1/2	3/4
<b>208420</b>	FRP-4080-300E	300	2	4.00 / 101.60	80.00 / 2032	3/4	1/2	3/4