



CONVECTION OVENS

BAKERLUX SHO??ro

Heavy-duty digital touch countertop convection oven with humidity

Side door: RIGHT to LEFT opening



ROSSELLA.MATIC

Full Size (4 Shelves)

LEFT to RIGHT opening

Side door:



ROSSELLA.MATIC

Full Size (4 Shelves)

Front door: TOP to BOTTOM opening



ROSSELLA

Full Size (4 Shelves)

Front door: TOP to BOTTOM opening



ARIANNA

Half Size (4 Shelves)

XAFT-04FS-ETRV

- Power: 208-240V, 7600W, 32A, 6-50P
- Panel: TOUCH Save up to 99 programs with graphic control panel. USB, WIFI
- Cooking Chamber: 27.2" W x 13.2" H x 19" L (includes 4 x wire shelves)
- Dimension: 31.5" W x 19.8" H x 35.5" L
- Net Weight: 140 lbs • Ship Dimensions:
- 42" W x 26.2" H x 48" L • Ship Weight: 190 lbs
- 2 fans, 2 speeds
- Interior LED light
- Auto shut off when door is opened
- Includes electro valve for direct plumbed water connection
- Cool touch double door

XAFT-04FS-ETLV

- Power: 208-240V, 7600W, 32A, 6-50P
- Panel: TOUCH Save up to 99 programs with graphic control panel. USB, WIFI
- Cooking Chamber: 27.2" W x 13.2" H x 19" L (includes 4 x wire shelves)
- Dimension:
 - 31.5" W x 19.8" H x 35.5" L
- Net Weight: 140 lbs
- Ship Dimensions: 42" W x 26.2" H x 48" L
- Ship Weight: 190 lbs
- 2 fans, 2 speeds
- Interior LED light
- · Auto shut off when door is opened
- Includes electro valve for direct plumbed water connection
- Cool touch double door

XAFT-04FS-ELDV

- Power: 208-240V, 7600W, 32A, 6-50P
- Panel: LED Save up to 99 programs including 12 quick access. USB, WIFI
- Cooking Chamber: 27.4" W x 13.2" H x 17.4" L (includes 4 x wire shelves)
- Dimension: 31.5" W x 19.6" H x 35.5" L
- Net Weight: 140 lbs
- Ship Dimensions: 42" W x 26.2" H x 48" L
- Ship Weight: 190 lbs
- 2 fans, 2 speeds
- Interior LED light
- · Auto shut off when door is opened
- Includes electro valve for direct plumbed water connection
- Cool touch double door

XAFT-04HS-ETDV

- Power: 208-240V, 3800W, 16A, 6-20P
- Panel: TOUCH Save up to 99 programs with graphic control panel. USB, WIFI
- Cooking Chamber: 19.2" W x 13.2" H x 14" L (includes 4 x wire shelves)
- Dimension: 23.6" W x 19.6" H x 29" L
- Net Weight: 93 lbs
- Ship Dimensions: 42" W x 26.2" H x 48" L
- Ship Weight: 139 lbs
- 1 fan, 2 speeds
- Interior LED light
- · Auto shut off when door is opened
- Includes electro valve for direct plumbed water connection
- Cool touch double door

Optional Accessories (FULL SIZE)

XAKPT-08FS Proofer, XAKRT-08FS Stand, XWKQT-04EF Stacking Kit, XAKHT-HCFS Ventless Hood, XHX010 "Bakery Pure 50" filtering system, XHX011 Refill "Bakery.Pure.50" filtering system

Optional Accessories (HALF SIZE)

XWKRT-08HS Stand, XWKQT-00HS Stacking Kit, XAKHT-HCHS Ventless Hood. XHX010 "Bakery.Pure.50" filtering system, XHX011 Refill "Bakery.Pure.50" filtering system







Warranty (1) year parts and labor

TOUCH



LED



GRILLS AND TRAYS




Perforated aluminum pan for pastry and bakery products

TG310

• 18" x 13" x 0.6" H

TG515

• 18" x 26" x 0.6" H



Flat chromium plated replacement racks

GRP305

• 18" x 13" • 18" x 26"



"BLACK BAKE" Perforated aluminum non-stick pan for pastry and bakery products

TG330

• 18" x 13" x 0.6" H

TG520

• 18" x 26" x 0.6" H



GRP310

• 18" x 13



"FAKIRO" Flat aluminum plate for pizza and foccacia

TG335

TG440

• 18" x 13"

• 18" x 26"



"NO.FRY" Stainless steel pan for French fries

GRP350

• 18" x 13

PROOFER



These proofers are not stand-alone items. They can only be run and controlled when stacked in modular confirguration with the BAKERLUX digital convection oven (LED or TOUCH control panels).

XAKPT-08FS

- Capacity: 8 full size sheet pans (not included)
- Heat settings: from 90°-122°F (32°-50°C)
- Power: 208-240V, 1300W, 5.5A, 6-15P
- Dimension: 31.5" W x 35.4" H x 31.1" L
- Net weight: 82 lbs
- Ship Dimensions: 42" W x 37" H x 48" L
- Ship weight: 137 lbs

Requires a water supply for humidity compatible ovens:

XAFT-04FS-ELDV XAFT-04FS-ETRV XAFT-04FS-ETLV





Warranty (1) year parts and labor

ACCESSORIES



Bakerlux Ventless Hoods

Vapor capture and condensing system. Removes odors and grease laden vapors expelled. No outside venting required Certified ANSI UL 710B approved circulating hood system

XAKHT-HCFS

- Ventless Hood (Full size)
- Power: 208-240V, 200W, 1A, 6-15P
- Dimension: 31.2" W x 10.2" H x 34" L
- Net weight: 65 lbs
- Ship Dimensions: 33.5" W x 10.8" H x 37" L
- Ship weight: 77 lbs

XAKHT-HCHS

- Ventless Hood (Half size)
- Dimension: 23.6" W x 9.8" H x 28.7" L
- Net weight: 45 lbs
- Ship Dimensions: 25.2" W x 10.8" H x 28.7" L
- Ship weight: 55 lbs











UL 710B EMISSIONS

Warranty (1) year parts and labor



High Open Stand with Lateral **Supports**

XAKRT-08FS

- Capacity: 8 shelves: 26"x18" (Full size)
- Pitch: 2.3"
- Net weight: 22 lbs
- Ship Dimensions: 31.2" W x 29" H x 27" L

XWKRT-08HS

- Capacity: 8 shelves: 13"x18" (Half size)
- Pitch: 2.3"
- Net weight: 20 lbs
- Ship Dimensions: 23.3" W x 29" H x 21.5" L





Warranty (3) months

> Filtering System and Recharge



Stacking Kits

Double stack installation kit. Includes all parts and connections for stacking 2 ovens.

Everything needed to securely stack one oven on top of another and protect the top oven's control panel from heat rising from bottom oven.

XWKQT-04EF

• Bakerlux Stacking Kit (Full size)

XWKQT-00HS

• Bakerlux Stacking Kit (Half size)

Warranty (3) months



XHC010

• "Bakery.Pure.50" filtering system

XHC011

• "Bakery Pure 50" filtering system refill



Please consult our web site www.eurodib.com for additional information on other product lines. CANADA 120 rue de la Barre, Boucherville, Qc J4B 2X7

Tel.: 1888 956 6866 | info@eurodib.com | www.eurodib.com