

ESM14SL60HC

*Impulse Cold Space Merchandiser®
Double Sliding Door*

Project Name: _____

Item #: _____ Quantity: _____



| Width* | Depth** | Height*** | Shelves | Cold Space™ | Ship Weight | Ship Cube | Cooling Capacity | Electrical |
|----------------|---------------|----------------|---------|-------------|-------------------|----------------------|------------------|---|
| 47" 1194 mm | 21" 534 mm | 60" 1524 mm | 8 | 20.4 | 304 lbs 138 kg | 43 cu. ft 1.22 m³ | 1/4 HP | 115V/3.5Amp/60 Hz - Single Phase - NEMA 5-15P, Dedicated Circuit |

** Add 7/8" (23mm) for Door Handle and 1" (26mm) for Power Cord – O/A 1 7/8" (48mm). *** Add 3/8" (10mm) for Threaded-In Levelers. Millimeters rounded up. Shipped less Graphics. Custom Graphics Optional.

| Flat Shelf 20 oz /600ml | | Gravity GlideSet™ 20 oz /600ml | | Trailerload Quantity (53') |
|-------------------------|---------|--------------------------------|---------|----------------------------|
| Packout | Facings | Packout | Facings | |
| 280 | 14 | 240 | 12 | 48 |

Premium Features



Cassette® Refrigeration



Finless Free&Clear™
Condenser Coil



LED Lighting System



Easy-Glide Door System



Automatic Stainless Steel
Condensate Control System



Front Breathing Refrigeration



Priority Air-Flow




HABCO
Insulated Glass

ESM14SL60HC: Designed to optimize impulse merchandising experience to the highest standards of quality and performance.

Refrigeration:

- Self contained Cassette® forced-air refrigeration employs R290 hydrocarbon Natural Refrigerant within a sealed capillary tube system.
- Cassette® refrigeration is bottom-mounted and removable from the front for ease of maintenance. Refrigeration may be exchanged or upgraded without mechanic. Designed to operate at a set point between 34°F to 39°F (1°C - 4°C).
- Priority, directed air flow provides optimum cooling and energy efficiency within cabinet and exclusively at front of unit for optimized heat exchange ventilation.
- Finless, Free&Clear™ Condenser Coil maximizes air-flow over the compressor, reduces energy consumption and is non-clogging.
- Automatic, stainless steel condensate control system.
- Quality, self-lubricating and sealed motors with streamlined air-flow provide quieter yet robust refrigeration.



Cabinet:

- Exterior – durable textured black.
- Interior – NSF approved white aluminum liner with stainless steel floor.
- Ergonomic raised interior floor.
- Space Saving Design – air ventilation exclusively from the front of unit.
- Insulation – cabinet is foamed-in-place with eco-conscious, polyurethane insulation.
- Heavy duty thread-in leveler legs.

Doors:

- Easy-Glide, Self-Closing Sliding Doors are suspended on large nylon-tired roller bearings, with spring assist and magnetic cabinet side seals.
- Magnetic gaskets are single piece bead-mount construction easily removable for cleaning.
- Heat Reflecting HABCO Insulated Safety Glass with black extruded frame.
- Durable, injection molded external door handle(s).

Lighting:


- LED Lighting System for Brilliant Illuminated Interior Display and Available Backlit Door Merchandising, on Switch.

Storage:

- Eight (8) white coated shelves 20 7/8"W x 14 3/4"D (531mm x 375mm), are NSF approved.
- Heavy duty aluminum shelving pilasters will not peel or chip adjustment of 1/2" (13mm) increments.
- NSF-7 compliant for storage or display of pre-packaged aseptic product.

Electrical:

- Factory power cord installed for connection to a sole-use (dedicated) 115V/60Hz/1-Phase, 15 Amp circuit.



HABCO MANUFACTURING INC. 501 GORDON BAKER ROAD, TORONTO, ONTARIO, CANADA, M2H 2S6
 Toll Free CAN: 1-800-387-5398 USA: 1-800-448-0244 Fax: 416-491-6982 www.habcomfg.com