





minipack[®]
america

1832 North Glassell Street · Orange, CA 92865, USA
Call: +1 (714) 283-4200 · Fax: +1 (714) 283-4268
info@minipack.us · www.minipack.us

MVS 41X



Chamber & Seal Bars	
Chamber Width x Length	29" x 13.5"
Height (Chamber + Dome/Lid = Total)	3" + 1" = 4"
Number of Seal Bars	3
Position of Seal Bars	Front, Left & Right
Seal Bar Length	24.75" (F) / 2 x 12.25" (L & R)
Distance between Seal Bars	25" (Left to Right)
Seal: Flat (4mm) + Bag Trimmer	✓
Unique Waffle-Pattern Sealing	✓
Hygienic Seamless Chamber	✓
Pop-Out Seal Bars	✓
Independent Power to each Seal Bar	✓
Performance	
Pump Type	Busch KB Oil Rotary
Cycles per Minute*	up to 3
Free Air Displacement	20 m ³ /h
Pump Power Rating	1.25 hp
Power Supply	120V / 19A
Display & Controls	
Water Resistant Digital Display	✓
LED Display	✓
Electronic Millibar Sensor	✓
Customizable Programs	9
Operational Features	
Programmable Sealing Time	✓
Programmable Vacuum Time (%)	✓
Extra Vacuum (30 sec)	✓
Excess Bag Cut-Off	✓
High Volume Density Plates	✓
Service	
Indicating Display	✓
Programmable Service Reminder	✓
1 Year Limited Warranty	✓
Housing & Dimensions	
Material	Stainless 304
Lid Type	Transparent with Dome
Width x Length	34" x 20.5"
Height (Lid open/closed)	28" / 17"
Recessed Lifting Cups	✓
Leveling Legs	✓
Shipping Wt.	245lbs
Certificates	
ETL Electrical	 Electrical Approved
ETL Sanitation (NSF Standard)	 Sanitation Approved
Optional Seal Bars	
Liquid & Foil Bag Seal	✓
Optional Features	
Gentle Air Return	✓
Elevated Legs	✓
Inert Gas Kit (5 Nozzles)	✓
230V / 1ph / 10A / 20 m ³ /h	✓

*Depends on type of product, film and operator ability.
Specifications may change without notice.