

MEDIUM DUTY PAN RACKS STAINLESS STEEL END LOAD

- Material: stainless steel construction, 1" tubing, Runner angles 1" x 1-1/2"
- **Lifetime Warranty Against Rust**
- Application: For proofing, storage and transporting finished product on 18" x 26" and 14" x 18" pans and trays.
- Holds: End Load holds (1) 18" x 26" full sheet pans; Side Load holds (2) 18" x 14" half sheet pans
- Rolls easily on heavy duty 5" polyurethane swivel stem casters
- Rolling Capacity: **800 lbs**
- Weight Capacity per Runner: **30 lbs**

Model Number	Order#	Overall Dimensions			Pan Cap. 18"x26"	Runner Spacing (in)	Approx. Ship Wt (lb)
		Width	Length	Height			
		(in)	(in)	(in)			
SS-1810B	110470	21	26	69¾	10	6	42
SS-1812B	110488	21	26	69¾	12	5	51
SS-1818B	110525	21	26	69¾	18	3	65
SS-1820B	110541	21	26	69¾	20	3	70
SS-1830B	110568	21	26	69¾	30	2	90

Caster information:
Caster with 5" Polyurethane Wheel 757 (123684)
5" Polyurethane Wheel 7112 (122180)

Freight Class: 250

Options:

- B** Bumpers (4)
- BP** Plate Casters 5" Polyurethane Wheel
- LC** Locking Casters
- TG-SS** Tray Guard/Stainless Steel
- KD** Knock-Down Design
- CORR** Correctional Package
- XB** XHD Reinforced Upright



SS-1820B

MEDIUM DUTY PAN RACKS STAINLESS STEEL SIDE LOAD

- Material: stainless steel construction, 1" tubing, Runner angles 1" x 1-1/2"
- **Lifetime Warranty Against Rust**
- Application: For proofing, storage and transporting finished product on 18" x 26" pans, side loading.
- Holds: Side Load holds (2) 18" x 26" half sheet pans
- Rolls easily on heavy duty 5" polyurethane swivel stem casters
- Rolling Capacity: **800 lbs**
- Weight Capacity per Runner: **30 lbs**

Model Number	Order#	Overall Dimensions			Pan Cap. 18"x26"	Runner Spacing (in)	Approx. Ship Wt (lb)
		Width	Length	Height			
		(in)	(in)	(in)			
SS-2610B	110584	28	18	69¾	10	6	76
SS-2618B	156339	28	18	69¾	18	3	38
SS-2620B	110605	28	18	69¾	20	3	97

Caster information:
Caster with 5" Polyurethane Wheel 757 (123684)
5" Polyurethane Wheel 7112 (122180)

Freight Class: 250

Option:

- XB** XHD Reinforced Upright



SS-2610B