## **MEDIUM DUTY PAN RACKS - SIDE LOAD**

■ Material: Aluminum, all welded. Runner angle 1" x 1-1/2"

■ Life time Warranty Against Rust

Application: Proof, store and transport finished product holds full size sheet pans. loading on the 26" side.

Holds:

18" x 26" Sheet Pans

■ Casters: 5" Polyurethane Swivel Stem

■ Rolling Capacity: 800 lbs.

Weight Capacity Per Runner: 30 lbs

		Overall Dimensions			Pan	Runner	Approx.
Model Number	Order#	Width	Length	Height	Сар.	Spacing	Ship Wt.
Number		(in)	(in)	(in)	18"x26"	(in)	(lb)
AL-2610B	110251	28	18	69¾	10	6	18
AL-2612B	110269	28	18	69¾	12	5	21
AL-2615B	110293	28	18	69¾	15	4	23
AL-2618B	110322	28	18	69¾	18	3	24
AL-2620B	110349	28	18	69¾	20	3	26

Caster information:

Caster with 5" Polyurethane Wheel 757 (123684)

5" Polyurethane Wheel 7112 (122180)

Freight Class: 250

## **Options:**

SB

В Bumpers (4) ВP

Plate Casters 5" Polyurethane Wheel

LC Locking Casters TG-AL Tray Guard/Aluminum KD Knock-Down Design

Aluminum Solid Bottom

PP Prison Package ΧB

XHD Reinforced Uprights





## **HEAVY DUTY** PAN RACK - END LOAD

■ Material: Aluminum, all welded 1" tubing. Runner angle 1"x1-1/2"

■ Lifetime Warranty Against Rust

Application: Heavy duty rack proof, store and transport full size sheet pans or half size sheet pans. Ideal for schools, restaurants, catering, banquet halls.

Holds:

18" x 26" Sheet Pans 14" x 18" Sheet Pans

■ Casters: 5" Polyurethane Swivel Stem

■ Rolling Capacity: 800 lbs.

Weight Capacity Per Runner: 60 lbs

		Order#	Overall Dimensions					Approx.
	Model Number		Width	Length	Height	Сар.	Spacing	Ship Wt.
	Hamber		(in)	(in)	(in)	18"x26"	(in)	(lb)
Ī	AL-1820B-XB	647023	21	26	69¾	20	3	34

Caster information:

Caster with 5" Polyurethane Wheel 757 (123684)

5" Polyurethane Wheel 7112 (122180)

Freight Class: 250

## **Options:**

Aluminum Solid Bottom Bumpers (4) SR ВP Plate Casters 5" Polyurethane Wheel Prison Package

LC Locking Casters TG-AL Tray Guard/Aluminum Knock-Down Design

In line with our policy to continually improve our products, Winholt reserves the right to change materials and specifications without notice.





AL-2612B



