



FEATURES

TPD PORTABLE LUXUS® THERMAL DISPENSERS



TECHNOLOGY YOU CAN COUNT ON

This rugged 1.5 gallon size dispenser is compatible with all FETCO 1.5 and 2x1.5 gallon EXTRACTOR®, Handle Operated and IP44/Maritime series brewers. The TPD series is a great choice in that it allows you to confidently extend your high-quality beverage service into virtually any remote indoor/outdoor venue or service environment.



DURABILITY

The durable stainless steel outer body construction withstands harsh conditions associated with daily use, cleaning, handling and transportation.



PORTABILITY

Designed for portability, each dispenser features 2 vertical comfort-grip carry handles mounted permanently to the sides with an additional handle built in to the locking twist top cover.



VISIBILITY

Front-mounted sight glass allows the operator to monitor internal liquid levels to help maintain uninterrupted beverage service.



FRESHNESS

Lock in freshness, flavors and maximum holding temperatures during transportation with the exclusive twist top cover with a safety lock feature.



QUALITY

The interior construction features a high-quality stainless-steel liner with superior insulative properties for optimum retention of hot or cold temperatures.



SAFETY

A built-in faucet guard helps prevent cross-contamination by keeping container lids away from the spout.

DISPENSERS

TPD PORTABLE LUXUS® THERMAL DISPENSERS





ACCESSORIES

TPD PORTABLE LUXUS® THERMAL DISPENSERS

WATER FILTRATION SYSTEM

Filtration System	Item Number	Item Description	Rated Capacity	Working Pressure	Weight
Everpure®	A039	In-Line System	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
Everpure®	A075	Replacement Cartridge	113,563 liters	10-125 psi [0.7-8.6 bar], non-shock	6.0 lbs / 2.7 kg
BWT Bestmax	A138	In-Line System	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A139	Replacement Cartridge	3,002 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A140	In-Line System	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg
BWT Bestmax	A141	Replacement Cartridge	4,562 liters	29-116 psi [2-8 bar], non-shock	11.0 lbs / 5.0 kg

EVERPURE®

In-Line Water Filtration System



SET INCLUDES: 1ea. commercial quality corrosion resistant filter head 1ea. taste and odor filter cartridge (FETCO® #A075) / 1ea. 3/8" x 4' connection hose / 1 set — mounting bracket and hardware.

- Recommended for large-sized operations
- Taste and odor filter for extremely turbid (cloudy) water
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head inlcudes built-in shutoff valve

BWT BESTMAX

In-Line Water Filtration System



SET INCLUDES: 1ea. filter cartridge / 1ea. universal filter head / 1ea. wall mounting bracket Braided hose supplies 3/8" and 3/4" compression, in 24" or 48" lengths

- Recommended for small- to medium-sized operations
- Carbonate hardness removal prevents scale deposits and retains minerals
- Granular-activated carbon reduces sediment and chlorine
- Quick-disconnect style head/cartridge design cartridge for effortless replacement
- Durable, corrosion-resistant head inlcudes built-in shutoff valve
- Four bypass settings allows for different water qualities and product preferences

DIMENSIONS

TPD-15 1.5 GALLON LUXUS® PORTABLE THERMAL DISPENSER

DIMENSIONS					WEIGHT		
[in] / [cm]	Height (A)	Width (B)	Depth (C)	Faucet Clearance (D)	[lbs] / [kg]	Empty	
Product Dimensions	24.2 61.3	9.4 23.7	13.8 35.2	7.0 17.8	Product Weight	12.7 5.8	
Shipping Dimensions	26.0 66.0	10.0 25.5	14.0 36.0	N/A	Shipping Weight	15.0 6.8	

TPD-30 3.0 GALLON LUXUS® PORTABLE THERMAL DISPENSER

DIMENSIONS					
[in] / [cm]	Height (E)	Width (F)	Depth (G)	Faucet Clearance (H)	
Product Dimensions	22.3 56.7	11.0 27.9	15.5 39.4	7.0 17.8	
Shipping Dimensions	28.0 71.0	16.5 41.5	14.0 36.0	N/A	

WEIGHT				
[lbs] / [kg]	Empty	Filled		
Product Weight	18.0 8.2	43.0 19.5		
Shipping Weight	21.0 9.5	N/A		

Filled

26.0 11.8

N/A



