

Always a spotless rotisserie

TDR 8 auto-clean



Save time, save costs and boost your sales with a spotless cooking theater that offers all the benefits of a traditional Fri-Jado rotisserie. Save at least one hour of labor every day as manually cleaning the rotisserie's cavity and accessories belongs to the past. The TDR auto-clean enables the operator to spend his valuable time on what's most important: serving customers.

The TDR 8 auto-clean reduces operational and maintenance costs. It has a surprisingly low water consumption: less than 6.6 gallon per cleaning cycle. It does not have any door seals that need frequent replacement. Our rotisserie cleaning tablets are safe to use for any operator.

With its compact dimensions, the TDR 8 auto-clean is likely to fit your store. It has an open cavity, providing the benefits of a traditional Fri-Jado rotisserie: preparing crispy and delicious rotisserie chickens that maintain their attractive appearance for hours.

Features TDR 8 Auto-Clean

Top features

- Easy-to-use: automatic cleaning
- Excellent cleaning with Fri-Jado Cleaning Tablets
- Unique: even accessories are cleaned
- Low water consumption: less than 6.6 gallon per cleaning cycle
- No door seals that need frequent replacement
- Controls with intelligent settings
- 250 programs with up to 9 cook stages per program
- Efficient heat transfer reduces energy consumption
- Cook Correction saves 5% on energy consumption and controls food safety

Standard characteristics

- Supplied on matching stand
- 7 Meat fork or V-spit positions, 7 basket or rack positions
- Rotor for up to 40 chickens (2.6 lbs) per batch
- USB connection for easy transfer of data and programs
- Boost functionality to add extra time if needed
- Outstanding food quality: high-speed convection for even cooking and radiant heat for uniform browning
- Appetising cooking theatre thanks to large glass surface and brilliant lighting

Accessories

- Meat fork
- Multi-purpose baskets
- V-spits
- Chicken racks




Intelligent controls



Auto-Clean function



Open cavity, no door seals



Even accessories are cleaned

TDR 8 Auto-Clean

Dimensions TDR 8 Auto-Clean including underframe

Width	41 inch
Depth	38 ½ inch
Depth with hood	42 ½ inch
Height	70 ½ inch
Height with hood	84 inch

Technical data TDR 8 Auto-Clean including underframe

Net weight	552 lbs
Gross weight	662 lbs
Voltage	3~ 208 V
Frequency	50/60 Hz
Power	12 kW
Plug	NEMA 15-50P

Additional Technical data

Water connection (aerated)	¾ inch
Min. water pressure	29 PSI (200 kPa)
Max. water pressure	72.5 PSI (500 kPa)
Acidity	7.0 - 8.0 pH
Chlorides	<30 ppm
Hardness*	<4 dH
Drain (open connection)	min. 1 5/8 inch

* Water hardness and descaling filters.

A descaling filter is advised when the hardness of the water is >4° dH (4 Grains/Gal). A descaling filter is mandatory when the hardness of the water is >20° dH (20 Grains/Gal).

Specifications and technical data are subject to amendment without prior notice.

These are basic drawings. For more detailed technical information, please refer to the installation manual at www.frijado.com.

