

KOLD-DRAFT

ice Machines • bins • crushers • dispensers



Plumbing:

- 3/4" FPT potable water inlet
- 3/4" FPT bin drain
- 3/4" I.D. flex tubing cuber drain
- 3/8" FPT condenser (liquid-cooled) inlet
- 1/2" FPT condenser (liquid-cooled) outlet

Exterior Finish:

300 Series stainless steel

Refrigeration System:


Thermostatic expansion valve controlled R-404A-HFC

Clearance Requirements:

Allow 4" left side, 8" right side and back, and 6" top for ventilation and utility connections.

Condenser Heat Rejection:

BTUH/kW/Ton
13,850/4.06/1.15 avg.
18,000/5.3/1.5 peak



IT'S NICE TO BE NOTICED™

X-SERIES

GBX1060 – ICE MACHINE

THE X-SERIES WORKHOUSE

Produces up to 1,000lbs of ice per day! The X-Series from Kold-Draft features rounded corners, plastic top panels, plastic louvers and an LCD display. X-Series machines are stackable with other X-Series machines. Double the capacity in the same footprint!

Dimensions/Weight

Description	Dimensions / inches (cm)			Ship Weight
	W	D	H	
Air Cooled	42.3" (107.4cm)	31.1" (79cm)	33.7" (85cm)	360lb (163.3kg)
Liquid Cooled	42.3" (107.4cm)	25.7" (65.3cm)	33.7" (85cm)	320lb (145kg)
Remote Air Cooled	42.3" (107.4cm)	25.7" (65.3cm)	33.7" (85cm)	320lb (145kg)

Recommended Operating Requirements:

	MIN.	MAX.
Room Air Temp.	45°F (7°C)	110°F (43°C)
Water Temp.	45°F (7°C)	90°F (32°C)
Voltage 208-230	198V	253V
Potable Water Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)
Liquid-Cooled Condenser Pressure	20 PSIG (137 kPa)	100 PSIG (689 kPa)

GBX1060 Series Daily Capacities: Lbs. of ice per 24 hours per unit

Model Number	Electrical Volt/Hz/Ph	Condenser	Cube Size	Ice Capacity 24 Hours lbs. (kg)		Energy Input 90°F (32°C) 70°F (21°C)	Water Use gal/100# (l/kg) 90°F (32°C) 70°F (21°C)		MCA	MOP	Required Condenser	
				70°F (21°C) 50°F (10°C) Ambient/ Water	90°F (32°C) 70°F (21°C) Ambient/ Water		Potable	Condenser				
GBX1064AC	208-230/60/1	Air Cooled	Full Cube	1075 (488)	860 (390)	4.9 (389)	12.9 (1.1)	n/a	11	20	n/a	
GBX1064AHK			Half Cube	1066 (484)	881 (400)	4.9 (389)	13.0 (1.1)		11	20		
GBX1064LC		Liquid Cooled	Full Cube	1047 (475)	918 (416)	4.1 (325)	16.4 (1.4)	174 (14.5)	10	20		
GBX1064LHK			Half Cube	1089 (494)	931 (422)	4.1 (325)	15.3 (1.3)	157 (13.1)	10	20		
GBX1064RC		Remote Air Cooled	Full Cube	959 (435)	767 (348)	5.3 (421)	12.6 (1.1)	n/a	11	25		RC314APV
GBX1064RHK			Half Cube	1031 (468)	838 (380)	5.1 (405)	15.0 (1.3)		11	25		

Use Model # GBX1067AHK, GBX1067AC, GBX1067LHK, GBX1067LC, GBX1067RHK, GBX1067RC to Indicate 220/50/1.

RC Condenser Series

Model Number	Description	Dimensions / inches (cm)			Gross Weight
		W	D	H	
RC314APV	Single-circuit vertical air flow remote condenser; vapor-charged with resealable quick-connect fittings, for GB1064R Cubers	40.75" (103.5cm) including interconnect fitting housing	22.75" (57.8cm)	30.2" (76.6cm) including 10" (25.4 cm) legs and fan guard	140lb (63.5kg)



COMPONENT

