

# Product data sheet

Specifications



## RACK PDU 2G, Switched, 5.7KW, 200/208V, (21) C13 & (3) C19 (BEING DISCONTINUED - SEE APDU9961)

AP8961

! Discontinued

! Discontinued on: Jun 13, 2022

! End-of-service on: Nov 9, 2022

## Overview

<b>Presentation</b>	APC Switched Rack Power Distribution Units (PDUs) enable advanced, user-customizable power control and active monitoring. Remote outlet level controls allow power on/off functionality for power recycling to remotely reboot equipment and restrict unauthorized use of individual outlets. Power sequencing delays allow users to define the order in which to power up or down attached equipment. Avoid circuit overload during power recovery and extend uptime of critical equipment by prioritizing the load shedding. Current metering provides real-time remote monitoring of connected loads. Switched Rack PDUs include real power monitoring, a temperature/humidity sensor port, locking IEC receptacles, and low profile circuit breakers. User-defined alarms warn of potential circuit overloads before critical IT failures occur. Users can access, configure, and control Switched Rack PDUs through secure Web, SNMP, or Telnet Interfaces and is complimented by APC Centralized Management platforms using InfraStruxure Central, Capacity Manager and Change Manager.
---------------------	---

**Lead time** Usually in Stock

## Main

<b>Color</b>	Black
<b>PDU Type</b>	Switched
<b>Cord length</b>	6 ft (1.8 m)
<b>Number of cables</b>	1
<b>Provided Equipment</b>	Installation guide Rack Mounting brackets Serial configuration cable Safety guide

## Complementary

<b>Input Voltage</b>	208 V 3 phase
<b>Height</b>	70.5 in (179.1 cm)
<b>Width</b>	2.2 in (5.6 cm)
<b>Output Voltage</b>	208 V
<b>Depth</b>	1.8 in (4.6 cm)
<b>Net Weight</b>	15.23 lb(US) (6.91 kg)
<b>mounting location</b>	Side
<b>Mounting preference</b>	No preference
<b>Input Plug Type</b>	NEMA L21-20P
<b>Mounting Mode</b>	Not rack-mountable

<b>Rack units</b>	0U
<b>USB compatible</b>	No
<b>Mounting position</b>	Vertical
<b>Line Rated Current</b>	16 A
<b>Max line current</b>	20 A
<b>Input current limits</b>	20 A
<b>Load Capacity</b>	5700 VA
<b>Input Frequency</b>	50/60 Hz
<b>Outlet type and quantity</b>	21 IEC 60320 C13 3 IEC 60320 C19

## Environment

<b>Product Certifications</b>	cUL Listed UL Listed VCCI Class A
<b>Standards</b>	FCC Part 15 class A ICES-003
<b>Ambient Air Temperature for Operation</b>	23.0000000000...140.0000000000 °F (-5...60 °C)
<b>Relative Humidity</b>	5...95 %
<b>Operating altitude</b>	0...10000 ft
<b>Ambient Air Temperature for Storage</b>	-13.0000000000...149.0000000000 °F (-25...65 °C)
<b>Storage Relative Humidity</b>	5...95 %
<b>Storage altitude</b>	0...50000 ft (0.0000000000...15240.0000000000 m)

## Ordering and shipping details

<b>GTIN</b>	731304277163
-------------	--------------

## Packing Units

<b>Unit Type of Package 1</b>	PCE
<b>Number of Units in Package 1</b>	1
<b>Package 1 Height</b>	78.8 in (200.2 cm)
<b>Package 1 Width</b>	4.5 in (11.4 cm)
<b>Package 1 Length</b>	6.5 in (16.5 cm)
<b>Package 1 Weight</b>	19.44 lb(US) (8.82 kg)

## Contractual warranty

<b>Warranty</b>	2 years repair or replace
-----------------	---------------------------

## Sustainability

**Green Premium™** label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

[Learn more about Green Premium >](#)



Energy Efficient Take-back

## Resource performance

✓ Energy Efficient Product

---

✓ Take-Back Program Available

---

## Well-being performance

✓ Lead Free

---

✓ Mercury Free

---

✓ Rohs Exemption Information [Yes](#)

---

**Eu Rohs Directive** Compliant with Exemptions

---