

Ultrafiltration System | UFL



Improve the quality of drinking water throughout the home and decrease the number of maintenance issues that are caused by poor water quality with the UFL ultrafiltration system.

The UFL systems feature an ultrafiltration cartridge that substantially reduces particles from the water. The system is self-cleaning, which extends the life of the ultrafilter and allows it to operate with little user intervention.

NOTE: The Flush Tank Kit (P/N 7000472) is highly recommended to improve the flushing function and extend the life of the ultrafilter.

NOTE: Additional taste and odor and scale reduction systems are also available.

FEATURES

- .015 micron ultrafiltration significantly reduces particles, assuring consistent, high- quality water.
- Self-cleaning capabilities extends the life of the ultrafilter.
- Operation simplicity.
- Several sizes available to meet various flow rates.



UFL-420, UFL-440 tested and certified by NSF International against NSF/ANSI:

Standard No. 42: Aesthetic Effects Nominal Particulate Reduction Class I.

Standard No. 53: Health Effects
Cyst Reduction Turbidity Reduction
as verified and substantiated by
test data.



Ultrafiltration System | UFL

UFL systems significantly reduce particles from water, yielding filtered water and fewer maintenance issues related to poor water quality. With a small footprint, these systems have added flexibility for easy installation.

Maximum Operating Pressure: 100 psig (690 kPa)

Maximum Operating Temperature: 104°F (40°C)

Nominal Pore Size: .015 microns

pH Range: 3 to 10 MWCO: 100 kD

Volts: 100 to 240

Watts: 10

Amps: 0.4

Includes plug adaptors for US, Europe, Australia, and UK

Specifications										
Model & Mfg. No.	Max. Flow Rate	UF Length	Inlet	Outlet	Drain	Width	Depth	Height	Operating Weight	Shipping Weight
UFL-410	4 gpm	10"	1"	1"	3/4"	10"	6 1/4"	20"	17 lbs.	19 lbs.
9700459	(15 lpm)	(25 cm)	MNPT	MNPT	FNPT	(25.4 cm)	(19 cm)	(51 cm)	(7.7 kg)	(8.6 kg)
UFL-420	5 gpm	20"	1"	1"	3/4"	11 1/2"	6"	28"	23 lbs.	23 lbs.
9700465	(19 lpm)	(51 cm)	MNPT	MNPT	FNPT	(29 cm)	(15 cm)	(71 cm)	(10.4 kg)	(10.4 kg)
UFL-440	10 gpm	40"	1"	1"	3/4"	11 1/2"	6"	47"	42 lbs.	33 lbs.
9700475	(38 lpm)	(102 cm)	MNPT	MNPT	FNPT	(29 cm)	(15 cm)	(119 cm)	(19.1 kg)	(15 kg)

Replacement Cartridges									
Name	Description	Mfg. No.							
L-410 Replacement Ultrafilter	for use in UFL-410	7000839							
L-420 Replacement Ultrafilter	for use in UFL-420	7000411							
L-440 Replacement Ultrafilter	for use in UFL-440	7000412							



P/N 1020250 07/17

China Facility

Toll Free: (800) 253-2991

Fax: (630) 784-1650