



## Nipples PVC, CPVC & PE Nipples



- PVC/CPVC Nipples furnished may be produced from extruded stock, or from molding grade PVC/CPVC compounds. Both processes provide quality products meeting ASTM requirements.
- Half Size Nipples not shown are priced the same as the next full size.  
For example: 7-1/2" is priced the same as 8".
- CONTACT YOUR LOCAL SPEARS® REPRESENTATIVE FOR PRICE AND AVAILABILITY OF SIZES, LENGTHS, AND/OR CONFIGURATIONS NOT SHOWN.

Length of Close & Short Nipples

Size	1/8"	1/4"	3/8"	1/2"	3/4"	1"	1-1/4"	1-1/2"	2"	2-1/2"	3"	4"	6"	8"	10"	12"
Close	3/4	7/8	1	1-1/8	1-3/8	1-1/2	1-5/8	1-3/4	2	2-1/2	2-5/8	2-7/8	3-3/4	3-5/8	4	4-3/8
Short	1-1/2	1-1/2	1-1/2	1-1/2	1-1/2	2	2	2	2-1/2	3	3	3-1/2	4-1/2	4-1/2	4-1/2	5

**THREADED CONNECTIONS** — Use a quality grade thread sealant. **WARNING: SOME PIPE JOINT COMPOUNDS OR PTFE PASTES MAY CONTAIN SUBSTANCES THAT COULD CAUSE STRESS CRACKING TO PLASTIC.** Spears® Manufacturing Company recommends the use of Spears® **BLUE 75™** Thread Sealant which has been tested for compatibility with Spears® products. Please follow the sealant manufacturers' application / installation instructions. Choice of an appropriate thread sealant other than those listed above is at the discretion of the installer. 1 to 2 turns beyond **FINGER TIGHT** is generally all that is required to make a sound plastic threaded connection. Unnecessary **OVERTIGHTENING** will cause **DAMAGE TO BOTH PIPE AND FITTING**.

**THIS PRODUCT IS ONLY TO BE USED FOR ITS INTENDED PURPOSE.**