

# Specification/Data sheet


## Integration kit for SelfCookingCenter® XS



Item number: 60.74.285

### Description

- For hygienic integration of a SelfCookingCenter® XS into a wall unit
- Integrated UltraVent XS absorbs and dissipates steam
- Eliminates the need for laborious installation of separate air extraction technology
- Targeted air direction ensures necessary cooling of the unit
- Stainless steel trim kit fulfils even the most stringent hygiene requirements
- Attractive design creates a professional, harmonious overall appearance
- Prevents build-up of soilage in difficult-to-reach places
- Easy to clean



### Technical information

- Connection: 125V 1 NAC 60 HZ
- Connected load: 225 W
- Air extraction rate: 9,900 - 20,000 ft³/h
- Operating noise level 1: 70 dBA
- For wall unit interiors 27 1/2" (700 mm) wide, 37 3/8" (950 mm) high, 23 5/8" (600 mm) deep
- Certification: VDE, UL
- Weight: 66 lbs (31kg)

### Equipment

- Easy-to-clean baffel plate (CNS)
- High-performance extraction
- Proximity door contact switch
- Extraction rate automatically increased when cabinet door is opened
- Wastewater discharged by the device - no additional discharge line needed
- Stainless steel trim kit

### Material

- Stainless steel

### Note

- Adhere to all local standards and regulations regarding installation and room ventilation systems
- Usable on units with either left-sided or right-sided hinges

# Specification/Data sheet

## Integration kit for SelfCookingCenter® XS

